000-221^{Q&As}

AIX 7 Administration

Pass IBM 000-221 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.lead4pass.com/000-221.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

What TWO situations require a Systems Director Management Console (SDMC) instead of a Hardware Management Console (HMC)? (Select 2)

A. Managing POWER5, POWER6 and POWER7 servers from one interface.

B. Creating automation plans that perform specific functions on a given event.

C. Implementing Active Memory Sharing (AMS).

D. Utilizing Integrated Virtualization Manager (IVM) to manage Power Systems blades.

E. Managing Power Blades and Power Systems standalone servers from one interface.

Correct Answer: BE

QUESTION 2

An administrator plans to duplicate the active rootvg on a given system to a spare disk that will be migrated to newer hardware. Which flag on \\'alt_disk_copy\\' must be used to reset user-defined device configurations to defaults?

A. X

B. R

C. O

D. D

Correct Answer: C

QUESTION 3

An administrator has logged in as root but is unable to run the ksh script named rperf. Given the following information, how could this be fixed?

A. Change the parent directory to be executable

B. Change the owner of the script to root

C. Change the file to be of extension ksh

D. Change the permissions to 700

Correct Answer: D

QUESTION 4

An administrator would like to update a VIO Server (VIOS) to the latest maintenance level. Which command, run from the restricted shell, will update the operating system on VIOS?

A. vios_update

B. update_all

C. install-all

D. updateios

Correct Answer: D

QUESTION 5

An administrator uses the \'no1 command to change the tcp_sendspace network tunable to 262144. A few minutes later, the ifconfig command produces the following output:

```
en0: flags=5e080863,c0<UP,BROADCAST,NOTRAILERS,RUNNING,SIMPLEX,MULTICAST,GROUPRT,
64BIT,CHECKSUM_OFFLOAD(ACTIVE),PSEG,LARGESEND,CHAIN>
        inet 10.126.0.5 netmask 0xffffff00 broadcast 10.126.0.255
        tcp_sendspace 131072 tcp_recvspace 65536 rfc1323 0
```

What additional action is needed?

A. Use ifconfig to cycle the interface down and up.

B. Run the no command again, specifying a permanent change.

C. Change the tcp_sendspace interface specific network option for the device.

D. Refresh inetd subsystem.

Correct Answer: C

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.lead4pass.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: