000-972^{Q&As}

000-972 Q&As

ILE RPG Programmer

Pass IBM 000-972 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.lead4pass.com/000-972.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

A database file contains two six digit fields named SHPDATE and DLVRYDATE, which contain date values in MMDDYY format.

Which of the following expressions will update the DaysToDeliver field, showing the number of days between SHPDATE and DLVRYDATE.

A. DaysToDeliver = %dec(%date(shpDate : *mdy)) - %dec(%date(dlvryDate : *mdy));

B. DaysToDeliver = %diff(%date(shpDate : *mdy) : %date(dlvryDate : *mdy) *days);

C. DaysToDeliver = %subdt(%date(shpDate : *mdy): %date(dlvryDate : *mdy) : *days);

D. DaysToDeliver = %date(shpDate : *mdy : *days) - %date(dlvryDate : *mdy : *days);

Correct Answer: B

QUESTION 2

Which of the following is an advantage gained by using %kds instead of a KLIST?

A. The ability to use date fields as keys

B. The ability to use array elements as keys

C. The ability to use a varying number of keys

D. The ability to test for an equal match on a SETLL operation

Correct Answer: C

QUESTION 3

Given the following code sample:

d address s 30 inz(\\'3207 North Henderson Parkway\\')

d addressChars s 1 dim(30)

c movea address addressChars

c move *blanks address

Which of the following would produce identical results?

A. d address s 30 inz(\\'3207 North Henderson Parkway\\') d addressChars s 1 dim(30) overlay(address) /free

%SubArr(addressChars : 1 : 30) = address; address = *blanks;

B. d addressarray ds d address 30 inz(\\'3207 North Henderson Parkway\\') d addressChars 1 dim(30) overlay(address) /free addressChars = address; address = *blanks;

C. d address s 30 inz(\\'3207 North Henderson Parkway\\') d addressChars s 1 dim(30)

/free addressChars = address;

address = *blanks;

D. d address s 30 inz(\\'3207 North Henderson Parkway\\') d addressarray ds d addressChars 1 dim(30) /free addressarray = address; address = *blanks;

Correct Answer: D

QUESTION 4

A programmer has just converted a subroutine to a subprocedure. When compiling the program with the CRTBNDRPG command, the compiler reports the following error:

RNF3788 Keyword EXTPGM must be specified when DFTACTGRP(*YES) is specified on the CRTBNDRPG command.

Which of the following keywords on an H spec in the program will resolve this error?

A. EXTPGM(*Yes)

B. EXTPGM(QILE)

C. DFTACTGRP(*No)

D. DFTACTGRP(QILE)

Correct Answer: C

QUESTION 5

Five existing programs are being converted for ILE. Two are to be bound into a service program and the other three are to be bound into a single program object, which uses the service program.

After the appropriate coding changes, which of the following is the correct sequence of commands required to create the program?

A. CRTSRVPGM, CRTPGM

B. CRTSRVPGM, CRTBNDRPG

C. CRTRPGMOD, CRTSRVPGM, CRTPGM

D. CRTRPGMOD, CRTPGM, CRTSRVPGM

Correct Answer: C

Latest 000-972 Dumps   000-972 Practice Test   000-972 Exam Questions