

# 132-S-900.7<sup>Q&As</sup>

Avaya IP Telephony Design Elective Exam

## Pass Avaya 132-S-900.7 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/132-s-900-7.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

Which three site survey factors should be used to measure the contours of Radio Frequency (RF) coverage? (Choose three.)

- A. link speed
- B. signal strength
- C. signal-to-noise ratio
- D. obstructions in the Fresnel Zone
- E. horizontal and vertical polarization

Correct Answer: ABC

---

## QUESTION 2

Currently, your customer has an S87xx series Media Server solution configured for high reliability. They have determined that they need critical reliability. What additional duplication is required?

- A. Server
- B. Bearer Network
- C. Control Network
- D. Digital Signal Processors

Correct Answer: B

---

## QUESTION 3

A sales engineer completes an S87xx Media Server/G650 Media Gateway design which includes IP Telephony, multi-locations, and LAN/WAN integration. One of the deliverables for handoff to the implementation team is the network region design. What four IP endpoint characteristics may be included in the network region design document? (Choose four.)

- A. codec set
- B. UDP port ranges
- C. 802.1p/Q settings
- D. VLAN assignments
- E. identification of locations

Correct Answer: ABCE

---

## QUESTION 4

A system needs to be upgraded from a G3csi system Release 10.1 to the current release of Avaya Communication Manager which is running on an S8500 with a G650 Media Gateway. You are provided a list of the cards in the system that includes:

four TN464 DS1 packs eight TN2224 digital station packs two TN793 analog packs one TN742 analog pack

What must you do to ensure the design will be a supported system? (Choose two.)

- A. add a TN799 Control-LAN (CLAN) interface
- B. determine specific hardware release information
- C. ensure all Ethernet connections are Cat5e compliant
- D. replace circuit boards that are below minimum vintage

Correct Answer: BD

---

## QUESTION 5

When carrying voice traffic over VPNs, what negatively affects voice performance? (Choose two.)

- A. Network Address Translation (NAT)
- B. The additional delay due to the encryption process
- C. An acceptable level of service with the VPN provider
- D. Excessive packet loss, delay, and jitter for traffic crossing the Internet

Correct Answer: BD

[132-S-900.7 PDF Dumps](#)

[132-S-900.7 VCE Dumps](#)

[132-S-900.7 Exam Questions](#)