

## 156-315.81<sup>Q&As</sup>

Check Point Certified Security Expert R81

### Pass CheckPoint 156-315.81 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/156-315-81.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by CheckPoint Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Sticky Decision Function (SDF) is required to prevent which of the following? Assume you set up an Active-Active cluster.

- A. Symmetric routing
- B. Failovers
- C. Asymmetric routing
- D. Anti-Spoofing

Correct Answer: C

---

**QUESTION 2**

Which is not a blade option when configuring SmartEvent?

- A. Correlation Unit
- B. SmartEvent Unit
- C. SmartEvent Server
- D. Log Server

Correct Answer: B

On the Management tab, enable these Software Blades:

---

**QUESTION 3**

By default how often updates are checked when the CPUSE Software Updates Policy is set to Automatic?

- A. Six times per day
- B. Seven times per day
- C. Every two hours
- D. Every three hours

Correct Answer: D

Reference: [https://sc1.checkpoint.com/documents/R77/CP\\_R77\\_Gaia\\_AdminWebAdminGuide/](https://sc1.checkpoint.com/documents/R77/CP_R77_Gaia_AdminWebAdminGuide/)

[html\\_frameset.htm?topic=documents/R77/CP\\_R77\\_Gaia\\_AdminWebAdminGuide/112109](https://sc1.checkpoint.com/documents/R77/CP_R77_Gaia_AdminWebAdminGuide/112109.html_frameset.htm?topic=documents/R77/CP_R77_Gaia_AdminWebAdminGuide/112109)

---

## QUESTION 4

What is the recommended way to have a redundant Sync connection between the cluster nodes?

- A. In the SmartConsole / Gateways and Servers -> select Cluster Properties / Network Management and define two Sync interfaces per node. Connect both Sync interfaces without using a switch.
- B. Use a group of bonded interfaces. In the SmartConsole / Gateways and Servers -> select Cluster Properties / Network Management and define a Virtual IP for the Sync interface.
- C. In the SmartConsole / Gateways and Servers -> select Cluster Properties / Network Management and define two Sync interfaces per node. Use two different Switches to connect both Sync interfaces.
- D. Use a group of bonded interfaces connected to different switches. Define a dedicated sync interface, only one interface per node using the SmartConsole / Gateways and Servers -> select Cluster Properties / Network Management.

Correct Answer: D

Explanation: The recommended way to have a redundant Sync connection between the cluster nodes is to use a group of bonded interfaces connected to different switches. In the SmartConsole / Gateways and Servers -> select Cluster Properties / Network Management, you should define a dedicated sync interface, only one interface per node.

---

## QUESTION 5

Which command would you use to set the network interfaces\' affinity in Manual mode?

- A. sim affinity -m
- B. sim affinity -l
- C. sim affinity -a
- D. sim affinity -s

Correct Answer: D

[Latest 156-315.81 Dumps](#)

[156-315.81 Study Guide](#)

[156-315.81 Braindumps](#)