

1Y0-241^{Q&As}

Deploy and Manage Citrix ADC with Traffic Management

Pass Citrix 1Y0-241 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/1y0-241.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Scenario: To receive data alerts for failures, a Citrix Administrator is configuring SNMP on the Citrix ADC. The administrator is confident that the manager, alarms and SNMP traps are configured correctly. The following week, there is a Citrix ADC-related outage and the administrator does NOT receive any alerts.

What could be the reason for this alert failure?

- A. The Citrix Web App Firewall is blocking the alerts from going out.
- B. The community name was NOT configured in the Citrix ADC SNMP trap destination settings.
- C. The Citrix ADC only has standard licensing.
- D. The Citrix ADC is configured for SNMP version 1.

Correct Answer: B

QUESTION 2

A Citrix Administrator wants to configure independent and isolated access on a single appliance to allow three different departments to manage and isolate their own applications. What can the administrator configure to isolate department-level administration?

- A. Admin partitions that use dedicated VLANs
- B. A SNIP in each partition, and bind a VLAN for the department
- C. Policy-based routes for each department in the nsroot partition
- D. Dedicated routes in the admin partitions for each department

Correct Answer: A

QUESTION 3

Scenario: In general, it is recommended to do the following:

Use _____ if you want the Citrix ADC to reset or drop a connection based on a client or request-based parameter.

Use _____ to redirect traffic or respond with custom messages.

Use _____ for manipulating data on HTTP requests and responses.

- A. rewrite, rewrite, responder
- B. responder, responder, rewrite
- C. rewrite, responder, rewrite
- D. responder, redirect, rewrite

Correct Answer: B

QUESTION 4

A Citrix Administrator needs to use a client's IP address as the source IP address for Citrix ADC-to-server connections. Which Citrix ADC mode can the administrator use to meet this requirement?

- A. USNIP
- B. Layer 2
- C. Layer 3
- D. USIP

Correct Answer: D

When you enable the USIP address mode of a NetScaler appliance, the appliance forwards each packet to the appropriate back end server with the client IP address. <https://support.citrix.com/article/CTX121974>

QUESTION 5

A Citrix Administrator needs to block all DNS requests from subnet 10.107.149.0/24. Which expressions can the administrator use to match the required traffic?

- A. CLIENT.IP.SRC(10.107.149.0) andand (client.UDP.DSTPORT.EQ(53) || client.TCP.DSTPORT.EQ(53))
- B. CLIENT.IP.SRC IN_SUBNET(10 107.149.0/24) andand client.UDP.DSTPORT.EQ(53) || client.TCP.DSTPORT.EQ(53)
- C. CLIENT.IP.SRC(10.107.149.0) andand client.UDP.DSTPORT.EQ(53) || client.TCP.DSTPORT.EQ(53)
- D. CLIENT.IP.SRC IN_SUBNET(10.107.149.0/24) andand (client.UDP.DSTPORT.EQ(53) || client.TCP.DSTPORT.EQ(53))

Correct Answer: D

[1Y0-241 PDF Dumps](#)

[1Y0-241 Practice Test](#)

[1Y0-241 Braindumps](#)