

1Y0-A21^{Q&As}

Basic Administration for Citrix NetScaler 9.2

Pass Citrix 1Y0-A21 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/1y0-a21.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Scenario: An administrator has set up a NetScaler in HA mode and now wants to bind the SSL certificate to one of the SSL virtual servers. However, the administrator notices that the command failed on the secondary node while succeeding on the primary node. Both nodes in HA are healthy, with successful configuration synchronization and command propagation.

Which reason explains the command failure on the secondary node?

- A. Command syntax is not correct.
- B. Command not executed with root ID.
- C. SSL command not available on secondary node.
- D. SSL certificate is not present on secondary node.

Correct Answer: D

QUESTION 2

Scenario: An administrator is working with a Citrix consultant to architect and implement a NetScaler solution. They plan to use GSLB and DNS views in the environment.

In which two manners can the administrator configure the NetScaler system to be able to configure DNS views that support GSLB records? (Choose two.)

- A. Configure as an ADNS.
- B. Configure as a DNS proxy.
- C. Configure CNAME records.
- D. Configure as an End resolver.

Correct Answer: AB

QUESTION 3

How can an administrator configure a health check for a server receiving HTTP traffic so that it monitors the response code of the server to actual client requests and NOT to probes whenever possible?

- A. Configure an HTTP-ECV monitor.
- B. Configure an HTTP-Inline monitor.
- C. Use the TCP monitor with the transparent parameter selected.
- D. Configure an HTTP monitor with the transparent parameter selected.

Correct Answer: B

QUESTION 4

An administrator set up a NetScaler pair in HA but later noticed that the configuration changes made on the primary node were NOT synchronized with the secondary node.

Which configuration setting must be corrected for successful configuration synchronization between both nodes in HA mode?

- A. HA monitoring on interfaces is set to off.
- B. HA monitoring on the node IDs is set to off.
- C. nsroot password is not identical for both nodes.
- D. RPC node password is not identical for both nodes.

Correct Answer: D

QUESTION 5

Scenario: An administrator plans to configure health checks for services bound to Web servers 1 and 2, which are listening on TCP port 80 for HTTP and TCP port 443 for HTTPS. Service1 receives the clear text traffic and Service2 receives the encrypted traffic.

Which type of monitor should the administrator bind to the services to meet the needs of this environment?

- A. A TCP monitor to Service1 and Service2
- B. An HTTP-ECV monitor to Service1 and Service 2
- C. An HTTPS monitor to Service1 and a HTTP monitor for Service2
- D. An HTTP monitor to Service1 and an HTTPS monitor to Service2

Correct Answer: D

[Latest 1Y0-A21 Dumps](#)

[1Y0-A21 Exam Questions](#)

[1Y0-A21 Braindumps](#)