

1Y0-A21^{Q&As}

Basic Administration for Citrix NetScaler 9.2

Pass Citrix 1Y0-A21 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/1y0-a21.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

How can an administrator configure a health check for a server receiving HTTP traffic so that it monitors the response code of the server to actual client requests and NOT to probes whenever possible?

- A. Configure an HTTP-ECV monitor.
- B. Configure an HTTP-Inline monitor.
- C. Use the TCP monitor with the transparent parameter selected.
- D. Configure an HTTP monitor with the transparent parameter selected.

Correct Answer: B

QUESTION 2

An administrator wants to configure a TCP service so that traffic can reach the associated server when the monitor assigned to the service is failing. Which attribute of the TCP service must the administrator configure to allow traffic to pass to the associated server in this scenario?

- A. Sure connect
- B. Access down
- C. TCP buffering
- D. Down state flush

Correct Answer: B

QUESTION 3

Which qualifier designates the source IP of the outgoing packet in a classic policy for NetScaler 9.2?

- A. RES.HTTP
- B. RES.SOURCEIP
- C. RES.IP.SOURCEIP
- D. RES.HTTP.HEADER
- E. RES.HTTP.SOURCEIP

Correct Answer: C

QUESTION 4

Scenario: An administrator configured the NetScaler system IP addresses for a newly installed system. The servers in this environment are located on separate subnets from the NetScaler appliance but are still routed through the NetScaler.

Which two configurations must the administrator ensure are configured on the NetScaler system so that it communicates correctly in this environment? (Choose two.)

- A. USIP mode is disabled.
- B. USNIP mode is enabled.
- C. SNIP on the NetScaler system is configured.
- D. A VIP on the same subnet as the NetScaler system has been created.

Correct Answer: BC

QUESTION 5

Scenario: An administrator must plan the deployment of a NetScaler system for an environment that requires:

- All traffic to pass through the NetScaler appliance(s)
- Outbound connections to the Internet from a non-routable subnet
- Two Web server farms to be load balanced by the fewest connections
-

All consumer web site traffic to be secured with SSL

All traffic to pass through a network firewall prior to passing through the NetScaler appliance(s)

- Fault tolerance
- Disabled traffic bridging on the NetScaler

Which three steps must the administrator take to deploy the NetScaler system correctly for this environment according to best practices? (Choose three.)

- A. Configure proxy mode.
- B. Configure Layer 2 mode.
- C. Configure RNAT functionality.
- D. Deploy the NetScaler system with HA.
- E. Enable Independent Network Configuration (INC).
- F. Deploy the NetScaler system in an inline configuration.

Correct Answer: CDF

[1Y0-A21 Practice Test](#)

[1Y0-A21 Exam Questions](#)

[1Y0-A21 Braindumps](#)