

1Z0-105^{Q&As}

Oracle Linux 6 Advanced System Administration

Pass Oracle 1Z0-105 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/1z0-105.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which three statements are true about the configuration and use of Kerberos with Oracle Linux? (Choose three.)

- A. Lightweight Directory Access Protocol (LDAP) authentication supports Kerberos authentication.
- B. Logins that are authenticated by Kerberos must be performed while connected to the network.
- C. Network Information Service (NIS) authentication supports Kerberos authentication.
- D. Winbind authentication supports Kerberos authentication by using the Active Directory Server (ADS) security model.
- E. Winbind authentication supports Kerberos authentication by using the Domain security model.
- F. Kerberos tickets are issued by the kadmind process that is running on the admin servers in the Kerberos realm.

Correct Answer: ACF

QUESTION 2

Consider the configuration requirements of an iSCSI client system.

Which statement is correct?

- A. Installation of the iscsi-initiatir-utils package is a prerequisite for configuration of an iSCSI client.
- B. Installation of both iscsi-target-utils and iscsi-initiator-utils are prerequisites for configuration of an iSCSI client.
- C. Installation of the iscsi-target-utils package is the only prerequisite for configuration of an iSCSI client.
- D. Both the iscsi-initiator-utils package and an iSCSI host bus adapter (HBA) hardware device are prerequisites for configuration of an iSCSI client.

Correct Answer: A

Reference: https://docs.oracle.com/cd/E52668_01/E54669/html/ol7-s17-storage.html

QUESTION 3

When you are using OCFS2, which two statements are true about Linux kernel configuration and use?

- A. kernel.panic_on_oops must be set to 1 to prevent a cluster hang.
- B. OSFS2 requires the use of the Red Hat compatible kernel.
- C. You must compile the OSFS2 module and make it available in the UEK kernel.
- D. OCFS2 requires the use of UEK3.
- E. kernel.panic must be set to 30 or higher.

Correct Answer: CD

QUESTION 4

Which statement is true about a general cgroup hierarchy?

- A. Any sgroup subsystems may be mapped to any cgroup hierarchies provided that a maximum of three cgroup subsystems are mapped to one cgroup hierarchy.
- B. A single cgroup hierarchy must have a maximum of one cgroup subsystem attached to it.
- C. A single cgroup hierarchy can have one or multiple sgroup subsystems attached to it.
- D. A single sgroup subsystem cannot be attached to multiple cgroup hierarchies.

Correct Answer: C

Reference: https://access.redhat.com/documentation/en-us/red_hat_enterprise_linux/6/html/resource_management_guide/ch01

QUESTION 5

While copying a file to the /users file system, which is located on /dev/sdd1, you receive an error:

```
$ cp /etc/oratab /users/oracle cp: cannot create regular file ` /users/oracle/oratab\\`: Disk quota exceeded You examine your assigned quota as shown: $ quota -q Disk quotas for user oracle (uid 500):
```

Filesystem	blocks	quota	limit	grace	files	quota	limit	grace
/dev/sdd1	2000	100000	20000		103*	100	150	6 days

Which option represents the reason for receiving the Disk quota exceeded error?

- A. The oracle user has reached its block quota.
- B. The oracle user exceeded its file quota five days ago.
- C. The oracle user has reached a group quota limit.
- D. The /users file system is full.
- E. The oracle user exceeded its block quota six days ago.

Correct Answer: C