201-450^{Q&As}

LPIC-2 Exam 201 Part 1 of 2 version 4.5

Pass Lpi 201-450 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.leads4pass.com/201-450.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Lpi Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

😳 365 Days Free Update

Leads4Pass

800,000+ Satisfied Customers



Leads4Pass

QUESTION 1

Which command can be used to scan a specified network looking for IP addresses that appear to be in use?

A. nmap

B. tcpdump

C. ip

- D. netscan
- E. hostdiscover

Correct Answer: A

QUESTION 2

What should be done after updating the configuration file for syslogd in order to make the changes become effective? (Choose TWO correct answers.)

- A. No action is required, syslogd will notice the updated configuration file after a few minutes.
- B. Send the HUP signal to the syslogd process.
- C. Restart the syslogd service.
- D. Run the command syslogd -u.

Correct Answer: BC

QUESTION 3

How is the source code for the main Linux kernel modules distributed?

- A. It is included with the Linux kernel source code.
- B. The kernel modules are downloaded on demand as they are used during compilation.
- C. The kernel modules have their own release cycle and can be maintained separately from the Linux kernel source.
- D. It is provided as a separate download alongside the Linux kernel source code of the same version.

Correct Answer: A

QUESTION 4

What does the -p3 option to the patch command do?

Leads4Pass

- A. It will strip off path information from each file mentioned in the patch file up to and including the third / character.
- B. patch continues execution as long as there are three or fewer errors.
- C. It instructs patch to look up to three lines of context before or after the declared line in the original file for a match.
- D. patch will keep three previous versions of each file in the output to prevent loss of change history.
- E. It instructs patch to conform more strictly to the POSIX standard.

Correct Answer: A

QUESTION 5

How can the label root be added to the ext2 filesystem on /dev/sda1?

- A. relabel /dev/sda1 root
- B. tune2fs -L root /dev/sda1
- C. echo \\'root\\' > /proc/fs/sda1/label
- D. labelfs --device /dev/sda1 root
- Correct Answer: B

Latest 201-450 Dumps

201-450 Practice Test

201-450 Braindumps