VCE & PDF
Lead4Pass.com

300-170^{Q&As}

Implementing Cisco Data Center Virtualization and Automation

Pass Cisco 300-170 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.lead4pass.com/300-170.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

Which description of the Visore tool is true?

A. It reports the current managed object in the bottom left hand corner of the GUI window.

B. It is a tool within UCS Director that allows the user to view the end point database.

C. It is an object store browser that exists on the APIC which can directly query the managed objects.

D. It is a tool used to report API calls that are made by the GUI to the APIC.

Correct Answer: C

Reference: https://www.cisco.com/c/en/us/support/docs/cloud-systems-management/application-policy-infrastructure-controller-apic/118839-technote-visore-00.html

QUESTION 2

In which configuration are atomic counters supported?

A. Endpoints in different VRFs

B. Endpoint-to-EPG policy in layer 2 scenario

C. Endpoints in different tenants

D. Endpoint-to-external IP address

Correct Answer: D

Reference: https://www.cisco.com/c/en/us/td/docs/switches/datacenter/aci/apic/sw/1-x/troubleshooting/b_APIC_Troubleshooting/b_APIC_Troubleshooting_chapter_0110.html

QUESTION 3

You plan to use L3Out connections when implementing Layer 3 multicast. Which statement about the router ID configuration is true?

A. The router ID must be unique for each L3Out on the same node in a VRF.

B. The router ID must be configured as a loopback address.

C. Each node in a VRF must use the same router ID.

D. The router ID must be an IPv4 address in a range of 224.0.0.0 - 239.255.255.255.

Correct Answer: B

QUESTION 4

You have an external switch that runs STP. An interface connected to the switch generates a loop_inc error. Which feature do you enable on the Cisco ACI fabric to resolve the issue?

A. LACP

B. MSTP

C. BPDU filter

D. PortFast

Correct Answer: C

QUESTION 5

You must apply a contract to all of the EPGs in a tenant. The solution must ensure that the contract is also applied to any new EPGs that are added to the tenant. Which options must you use?

A. the GUI

B. the vzAny managed object

C. the RESR API

D. a Python script

Correct Answer: B

[300-170 PDF Dumps](#)   [300-170 VCE Dumps](#)   [300-170 Braindumps](#)

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

https://www.lead4pass.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: