

300-425^{Q&As}

Designing Cisco Enterprise Wireless Networks (ENWLSD)

Pass Cisco 300-425 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/300-425.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which statement about creating a mobility group is true, excluding mobility anchors?

- A. Each WLC must use the same mobility name and be defined as a peer in each other's static mobility members list.
- B. If WLCs with HA SSO are deployed, each WLC in the WLC HA pair considered separately as a mobility peer.
- C. The WLCs do not have to be of the same model or type to be a member of a mobility group, however each member should be running different software versions.
- D. A mobility groups does not require all WLCs in the group to use the same virtual IP address.

Correct Answer: B

Reference:

- The HA pair of AireOS WLCs should be considered as separated WLCs with the same exact configuration

QUESTION 2

A customer has two Cisco 550B WLCs that manage all the access points in their network and provide N+1 redundancy and load balancing. The primary Cisco WLC has 60 licenses and the secondary Cisco WLC has 40. The customer wants

to convert the N+1 model to an HA model and provide SSO. Configuration must be performed during a maintenance window. After performing all the configurations on both controllers, the config redundancy unit secondary command is issued

on the secondary Cisco WLC and it fails.

Which parameter needs to be in place to complete the configuration?

- A. A cable in the RP port
- B. The secondary Cisco WLC needs a minimum of 50 base licenses
- C. The primary Cisco WLC is already set as the secondary unit.
- D. SSO needs to be enabled

Correct Answer: B

Reference:

- With Release 7.4, an HA-SKU secondary controller can be configured as a backup controller for N+1 HA. For example, the following can be used as an HA-SKU controller:
 - 5508 Series Standalone controller with 50 AP license

QUESTION 3

An engineer is designing a wireless network to support hyperlocation in an environment that already has APs installed. During the survey, the engineer notices that the APs are pointing in different directions. What is the recommended way to align the APs to easily determine AP Azimuth, X-Y, and ceiling height information, and minimize confusion and user-entered errors?

- A. APs must be aligned pointing toward the nearest wall.
- B. APs must be aligned pointing toward each other.
- C. APs must be aligned in the same direction.
- D. APs can be aligned all four ways.

Correct Answer: C

QUESTION 4

An enterprise has moved most services to the cloud, including email applications and real-time communication. Which feature must be enabled on the wireless network to improve the user experience?

- A. QoS
- B. Radio management
- C. Interference mitigation
- D. Fast secure roaming

Correct Answer: A

Reference: <https://community.cisco.com/t5/wireless-mobility-documents/what-is-cckm-and-how-does-it-affect-fast-and-secure-roaming/ta-p/3130421>

QUESTION 5

An engineer must perform a Layer 2 survey for a mining facility. Which type of antenna does the engineer use in the mine shaft?

- A. omnidirectional
- B. patch
- C. internal
- D. dipole

Correct Answer: A

[Latest 300-425 Dumps](#)

[300-425 Practice Test](#)

[300-425 Study Guide](#)