

300-430^{Q&As}

Implementing Cisco Enterprise Wireless Networks (ENWLSI)

Pass Cisco 300-430 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/300-430.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

An engineer configures a Cisco Aironet 600 Series OfficeExtend AP for a user who works remotely. What is configured on the Cisco WLC to allow the user to print a printer on his home network?

- A. split tunneling
- B. SE-connect
- C. FlexConnect
- D. AP failover priority

Correct Answer: A

Reference: <https://www.cisco.com/c/en/us/support/docs/wireless/aironet-602-officeextend-access-point/117540-configure-splittunneloeap-00.html>

QUESTION 2

A network engineer is implementing a wireless network and is considering deploying a single SSID for device onboarding. Which option is a benefit of using dual SSIDs with a captive portal on the onboard SSID compared to a single SSID solution?

- A. limit of a single device per user
- B. restrict allowed devices types
- C. allow multiple devices per user
- D. minimize client configuration errors

Correct Answer: B

<https://community.cisco.com/t5/security-documents/ise-byod-dual-vs-single-ssid-onboarding/ta-p/3641422>

QUESTION 3

An organization is supporting remote workers in different locations. In order to provide wireless network connectivity and services, OfficeExtend has been implemented. The wireless connectivity is working, but users report losing connectivity to their local network printers. Which solution must be used to address this issue?

- A. WLAN static IP tunneling
- B. FlexConnect local switching
- C. OEAP split tunnel
- D. OEAP gateway override

Correct Answer: C

QUESTION 4

A customer wants to Aps in the CEO's office to have different usernames and passwords for administrative support than the other APs deployed through the facility. Which feature must be enabled on the WLC and Aps to achieve this goal?

- A. Override global credentials
- B. 802.1X supplicant credentials
- C. Local management users
- D. HTTPS access

Correct Answer: B

QUESTION 5

A wireless administrator receives this information to complete a CMX deployment in high availability by using version 10.6 to gather analytics. IP address of the primary server IP address of the secondary server failover mode to be configured as automatic root password of the secondary server email ID for NOC notifications Enabling high availability fails when these parameters are used. Which action resolves the issue?

- A. Insert the cmxadmin password of the secondary server.
- B. Use IP protocol 4242 for the controller to reach the CMX server.
- C. Place primary and secondary servers in different subnets.
- D. Enable the virtual IP address of the primary server.

Correct Answer: A

[Latest 300-430 Dumps](#)

[300-430 VCE Dumps](#)

[300-430 Braindumps](#)