

300-430^{Q&As}

Implementing Cisco Enterprise Wireless Networks (ENWLSI)

Pass Cisco 300-430 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/300-430.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A company has a single WLAN configured for 802.1x authentication with the QoS set to Silver. This WLAN supports all corporate and BYOD access. A decision has been made to allow users to install Cisco Jabber on their personal mobile devices. Users report poor voice quality when using Jabber.

QoS is being applied only as best effort. What must be configured to ensure that the WLAN remains on the Silver class and to ensure Platinum class for Jabber?

- A. Configure an AVC profile for the Jabber traffic and apply it to the WLAN.
- B. Configure the WLAN to broadcast on 5 GHz radios only and allow Jabber users to connect.
- C. Enable Cisco Centralized Key Management on the WLAN so that the Jabber-enabled devices will connect.
- D. Configure QoS on the mobile devices that have Jabber installed.

Correct Answer: A

https://www.cisco.com/c/en/us/td/docs/wireless/controller/technotes/81/Jabber_in_WLAN/b_Jabber_in_WLAN.html#reference_7B4539C91FBE4639ACF906F6F3931667

QUESTION 2

An engineer is assembling a PCI report for compliance purposes and must include missed best practices that are related to WLAN controllers. The engineer has access to all WLCs, Cisco MSE, and Cisco Prime Infrastructure. Which method most efficiently displays a summary of inconsistencies?

- A. WLC running-config
- B. Cisco Prime Infrastructure monitoring
- C. Cisco Prime Infrastructure reporting
- D. WLC logs

Correct Answer: B

QUESTION 3

An engineer has configured passive fallback mode for RADIUS with default timer settings. What will occur when the primary RADIUS fails then recovers?

- A. RADIUS requests will be sent to the secondary RADIUS server until the secondary fails to respond.
- B. The controller will immediately revert back after it receives a RADIUS probe from the primary server.
- C. After the inactive time expires the controller will send RADIUS to the primary.
- D. Once RADIUS probe messages determine the primary controller is active the controller will revert back to the primary RADIUS.

Correct Answer: C

QUESTION 4

Which three properties are used for client profiling of wireless clients? (Choose three.)

- A. HTTP user agent
- B. DHCP
- C. MAC OUI
- D. hostname
- E. OS version
- F. IP address

Correct Answer: ABC

Reference: <https://www.cisco.com/c/en/us/td/docs/wireless/controller/technotes/7-5/NativeProfiling75.html>

QUESTION 5

A customer requires wireless traffic from the branch to be routed through the firewall at corporate headquarters. A RADIUS server is in each branch location. Which Cisco FlexConnect configuration must be used?

- A. central authentication and local switching
- B. central authentication and central switching
- C. local authentication and local switching
- D. local authentication and central switching

Correct Answer: D

[Latest 300-430 Dumps](#)

[300-430 Study Guide](#)

[300-430 Braindumps](#)