

300-625^{Q&As}

Implementing Cisco Storage Area Networking (DCSAN)

Pass Cisco 300-625 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/300-625.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



QUESTION 1

Which condition requires using a device alias rather than a Fibre Channel alias?

- A. The zone database must be distributed over the fabric.
- B. The same alias must be used in zoning as well as DPVM.
- C. All aliases being used are being configured in the same VSAN.
- D. Aliases must be saved within a central database on the fabric.

Correct Answer: A

QUESTION 2

Which configuration is needed to enable manual ESP mode for Fibre Channel TrustSec on Cisco MDS switches?

- A. MDS(config)# interface fc 1/1 MDS(config-if)# fcsp esp manual
- B. MDS(config)# fcsp esp manual
- C. MDS(config)# interface fc 1/1 MDS(config-if)# fcsp mode gcm MDS(config-if-fcsp)# fcsp esp manual
- D. MDS(config)# interface fc 1/1 MDS(config-if)# fcsp esp manual MDS(config-if-fcsp)# mode gcm

Correct Answer: A

QUESTION 3

Which action must be performed to deactivate a VSAN without losing its configuration?

- A. Isolate it.
- B. Delete it.
- C. Rename it.
- D. Suspend it.

Correct Answer: D

QUESTION 4

Which port mode is used on an NPV device to connect to an NPIV core switch?

- A. E
- B. F

C. N

D. NP

Correct Answer: D

QUESTION 5

Which two steps are mutual between Cisco secure boot and UEFI secure boot? (Choose two.)

A. bootloader

B. operating system

C. microloader

D. kernel

E. hardware anchor

Correct Answer: AB

[300-625 PDF Dumps](#)

[300-625 VCE Dumps](#)

[300-625 Braindumps](#)