

300-625^{Q&As}

Implementing Cisco Storage Area Networking (DCSAN)

Pass Cisco 300-625 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/300-625.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Refer to the exhibit.

Switch 1

```
Ivr nat
ivr vsan-topology auto
ivr service-group name GROUP1
autonomous-fabric-id 100 vsan-ranges 1-3, 100
autonomous-fabric-id 1 switch 20:00:00:05:31:11:32:ac vsan-ranges 1
autonomous-fabric-id 1 switch 20:00:00:05:40:12:1e:dd vsan-ranges 1-3
```

Switch 2

```
ivr vsan-topology auto
ivr service-group name GROUP2
autonomous-fabric-id 100 vsan-ranges 1, 6-7, 200
autonomous-fabric-id 1 switch 20:00:00:05:31:11:32:ac vsan-ranges 1
autonomous-fabric-id 1 switch 20:00:00:05:40:12:1e:dd vsan-ranges 6-7
```

What is the result of merging the fabric?

- A. The merged fabric IVR VSAN topology is set to activate.
- B. The merged fabric has NAT enabled.
- C. The merge is invalid.
- D. The merged fabric contains only service group Group1.

Correct Answer: D

QUESTION 2

Which feature on MDS platforms ensures that the code that is running on the hardware platform is authentic and unmodified, while also validating the BIOS to eliminate any rootkits.

- A. Cisco Secure Boot
- B. UEFI Secure Boot
- C. Secure Unique Device Identifier
- D. BIOS Secure Boot

Correct Answer: A

QUESTION 3

An engineer is configuring a SAN environment and attempts to activate a zoneset, but a lock is held by another user. Which argument does the engineer use to clear the lock from the zoning database configuration?

- A. commit
- B. abort
- C. clear
- D. force

Correct Answer: C

QUESTION 4

What does an unlicensed DCNM SAN fail to display?

- A. Fibre Channel, FCoE, and iSCSI topologies
- B. events and fault management
- C. historical performance monitoring
- D. real-time performance monitoring

Correct Answer: C

QUESTION 5

Which action must be performed to deactivate a VSAN without losing its configuration?

- A. Isolate it.
- B. Delete it.
- C. Rename it.
- D. Suspend it.

Correct Answer: D

[300-625 PDF Dumps](#)

[300-625 Practice Test](#)

[300-625 Braindumps](#)