

300-625^{Q&As}

Implementing Cisco Storage Area Networking (DCSAN)

Pass Cisco 300-625 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/300-625.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



QUESTION 1

Refer to the exhibit.

```
MDS-CORE# show running-config

role name VSAN-Admin
  rule 4 permit show
  rule 3 permit exec
  rule 2 permit debug
  rule 1 permit config
  vsan policy deny
```

A network engineer created a new user that uses the VSAN-Admin role on a Cisco MDS switch so a new colleague can manage the VSANs configured on the switch. Which action is required for the configuration to give permission to the new colleague?

- A. permit vsan 1-1000 must be configured as rule 5.
- B. permit vsan 1-1000 must be configured as rule 1.
- C. permit vsan 1-1000 must be configured under the VSAN policy deny.
- D. permit vsan 1-1000 must be configured under the VSAN policy allow.

Correct Answer: C

QUESTION 2

Which action must be performed to deactivate a VSAN without losing its configuration?

- A. Isolate it.
- B. Delete it.
- C. Rename it.
- D. Suspend it.

Correct Answer: D

QUESTION 3

Which EtherType is used by the FCoE Initialization Protocol?

A. 0x8913

B. 0x8914

C. 0xxfc0e

D. 0x8906

Correct Answer: B

QUESTION 4

A storage network engineer must install and configure a new MDS switch in a data center network. Which two statements about available choices during the MDS switch initial setup are correct? (Choose two.)

A. The engineer can choose what will be the administrator account.

B. The secure password standard is required.

C. The engineer can configure the default zone policy.

D. The engineer can configure the default switch port trunk mode.

E. The engineer does not have the choice to enable or disable full zoneset distribution.

Correct Answer: AC

QUESTION 5

Which two components are required for successful MDS USB POAP (Choose two.)

A. NTFS formatted USB drive

B. USB drive in port 1

C. script named poap_script.pl

D. ENTERPRISE_PKG license

E. system and kickstart images

Correct Answer: CE

[Latest 300-625 Dumps](#)

[300-625 PDF Dumps](#)

[300-625 Exam Questions](#)