

300-715^{Q&As}

Implementing and Configuring Cisco Identity Services Engine (SISE)

Pass Cisco 300-715 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/300-715.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Refer to the exhibit:

```
Interface: GigabitEthernet2/0/36
MAC Address: 000e.84af.59af
Status: Authz Success
Domain: DATA
Oper host mode: single-host
Authorized By: Authentication Server
Vlan Policy: 10
Handle: 0xE0000000
Runnable methods list:
Method State
dot1x Authc Success
```

Which command is typed within the CU of a switch to view the troubleshooting output?

- A. show authentication sessions mac 000e.84af.59af details
- B. show authentication registrations
- C. show authentication interface gigabitethemet2/0/36
- D. show authentication sessions method

Correct Answer: A

QUESTION 2

An organization has a fully distributed Cisco ISE deployment. When implementing probes, an administrator must scan for unknown endpoints to learn the IP-to-MAC address bindings. The scan is complete on one PSN, but the information is not available on the others.

What must be done to make the information available?

- A. Cisco ISE must be configured to learn the IP-MAC binding of unknown endpoints via RADIUS authentication, not via scanning.

- B. Cisco ISE must learn the IP-MAC binding of unknown endpoints via DHCP profiling, not via scanning.
- C. Scanning must be initiated from the MnT node to centrally gather the information.
- D. Scanning must be initiated from the PSN that last authenticated the endpoint.

Correct Answer: B

Reference: <https://community.cisco.com/t5/security-documents/ise-profiling-design-guide/ta-p/3739456>

QUESTION 3

An engineer is configuring a dedicated SSID for onboarding devices. Which SSID type accomplishes this configuration?

- A. dual
- B. hidden
- C. broadcast
- D. guest

Correct Answer: A

<https://community.cisco.com/t5/security-documents/ise-byod-dual-vs-single-ssid-onboarding/ta-p/3641422>

https://www.youtube.com/watch?v=HH_Xasqd9k4andab_channel=CiscoISE-IdentityServicesEngine
http://www.labminutes.com/sec0053_ise_1_1_byod_wireless_onboarding_dual_ssid

QUESTION 4

The security engineer for a company has recently deployed Cisco ISE to perform centralized authentication of all network device logins using TACACS+ against the local AD domain. Some of the other network engineers are having a hard time remembering to enter their AD account password instead of the local admin password that they have used for years. The security engineer wants to change the password prompt to "Use Local AD Password:" as a way of providing a hint to the network engineers when logging in. Under which page in Cisco ISE would this change be made?

- A. Work Centers> Device Administration Ext Id Sources>Advanced Settings
- B. The password prompt cannot be changed on a Cisco IOS device
- C. Work Centers> Device Administration> Network Resources> Network Devices
- D. Work Centers> Device Administration> Settings> Connection Settings

Correct Answer: D

QUESTION 5

Which type of identity store allows for creating single-use access credentials in Cisco ISE?

- A. OpenLDAP
- B. Local
- C. PKI
- D. RSA SecurID

Correct Answer: D

Reference: https://www.cisco.com/en/US/docs/security/ise/1.0/user_guide/ise10_man_id_stores.html

[Latest 300-715 Dumps](#)

[300-715 VCE Dumps](#)

[300-715 Study Guide](#)