

## 300-815<sup>Q&As</sup>

Implementing Cisco Advanced Call Control and Mobility Services  
(CLACCM)

**Pass Cisco 300-815 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/300-815.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



## QUESTION 1

What are the elements for Device Mobility configuration?

- A. physical location, device pool, and Device Mobility group
- B. device pool, Device Mobility group, and region
- C. physical location, Device Mobility group, and region
- D. device pool, Device Mobility group, and Cisco IP phone

Correct Answer: A

Reference: <https://www.ciscopress.com/articles/article.asp?p=1249228andseqNum=4>

---

## QUESTION 2

When configuring hunt groups, where does the administrator add the individual directory numbers that should be part of the group?

- A. route group
- B. line group
- C. hunt list
- D. hunt pilot

Correct Answer: B

Reference: [https://www.cisco.com/c/en/us/td/docs/voice\\_ip\\_comm/cucm/admin/12\\_0\\_1/systemConfig/cucm\\_b\\_system-configuration-guide-1201/cucm\\_b\\_system-configuration-guide-1201\\_chapter\\_010101.html](https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/admin/12_0_1/systemConfig/cucm_b_system-configuration-guide-1201/cucm_b_system-configuration-guide-1201_chapter_010101.html)

---

## QUESTION 3

An administrator is configuring a SIP trunk to an ITSP. The SIP connection will traverse from a Cisco UCM to the ITSP through a Cisco Unified Border Element. The ITSP has indicated that they require an in-band method for DTMF. Which command on the outbound dial-peer to the ITSP will meet this requirement?

- A. router (config-dial-peer) dtmf-relay sip-notify
- B. router (config-dial-peer) dtmf-relay sip-kpml
- C. router (config-dial-peer) dtmf-relay h245-alphanumeric
- D. router (config-dial-peer) dtmf-relay rtp-nte

Correct Answer: D

**QUESTION 4**

An engineer must implement call restriction to toll-free numbers using a class of restriction in a branch Cisco UCME. In which two places is the corlist incoming or cor incoming command configured? (Choose two.)

- A. "voice register pool " configuration mode
- B. "ephone-dn " configuration mode
- C. "dial-peer cor custom " configuration mode
- D. "voice register global " configuration mode
- E. "telephony-service " configuration mode

Correct Answer: AB

---

**QUESTION 5**

Refer to the exhibit.

```
CUBE_Router#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
CUBE_Router(config)#voice translation-rule 999
CUBE_Router(cfg-translation-rule)#rule 1 /^9(.*)/ //
CUBE_Router(cfg-translation-rule)#end
CUBE_Router#
CUBE_Router#test voice translation-rule 999 9123548
9123548 Didn't match with any of rules
```

Which change to the translation rule is needed to strip only the leading 9 from the digit string 9123548?

- A. rule 1 /^9(\d\*)/ \1/
- B. rule 1 /^9(.\*)/ \1/
- C. rule 1 /.\*(3548\$)/ \1/
- D. rule 1 /^9123548/ \1/

Correct Answer: B