

350-050^{Q&As}

CCIE Wireless Written

Pass Cisco 350-050 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.lead4pass.com/350-050.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



https://www.lead4pass.com/350-050.html

2021 Latest lead4pass 350-050 PDF and VCE dumps Download

QUESTION 1

Which two statements about the management access control on Cisco WLC, using an external TACACS+ server, are true? (Choose two.)

- A. The Cisco WLC supports TACACS+ command authorization.
- B. The Cisco WLC AAA authorization is role-based, using custom TACACS+ attributes.
- C. The Cisco WLC AAA authorization is role-based, using Cisco VSA attributes.
- D. The Cisco WLC requires the TACACS+ server to return a Privilege-Level attribute.
- E. If a user is not entitled to a specific task, then the user is not allowed to access that task.
- F. If a user is not entitled to a specific task, then the user is allowed to have read-only access to that task.

Correct Answer: BF

QUESTION 2

Which two methods can be used in Cisco Secure ACS 5.2 to assign client authentication requests to different access services or authorization policies, based on the SSID to which the client is associated? (Choose two.)

- A. DNIS-based end station filter
- B. CLI-based end station filter
- C. condition based on the RADIUS-IETF. Filter-ID(11) attribute
- D. condition based on the RADIUS-IETF: Called-Station-ID(30) attribute
- E. condition based on the RADIUS-IETF: Calling-Station-ID(31) attribute

Correct Answer: AD

QUESTION 3

Cisco WiSM controllers have multiple interface types. Which three statements about the interface types of the controllers are true? (Choose three.)

- A. The service-port interface is the default interface for in-band management of the controller.
- B. If the service port is in use, then the management interface must be on a different subnet than the service port.
- C. You cannot ping the AP-manager interface.
- D. The virtual gateway interface is used to support mobility management.
- E. The management interface is used as the source IP address for all Layer 3 communications between the controller and the lightweight APs.



https://www.lead4pass.com/350-050.html

2021 Latest lead4pass 350-050 PDF and VCE dumps Download

F. On the Cisco WiSM, the management interface is used to synchronize the supervisor engine and the Cisco WiSM.

Correct Answer: BCD

QUESTION 4

How can you improve location accuracy using RFID tags in RF-noisy or congested environments, such as hospitals?

- A. Repeat frame transmissions per channel within each transmission interval (although this will lower battery life).
- B. Transmit beacons as unicast instead of multicast, to make sure that APs can pick up the beacon packets.
- C. Decrease the inter-cell overlap to 5 percent, decreasing the uncertain area.
- D. Increase the data rate for the beacon packets to make sure that more data can be transmitted within the same time interval.

Correct Answer: A

QUESTION 5

A retail company is refreshing their WLANs in their stores. Costs, resiliency, and ease of management are all important design criteria. Which two statements are true when considering your proposed Cisco Unified Wireless solution? (Choose two.)

- A. FlexConnect (H-REAP) should be considered to manage the WLAN from a centralized controller. In the event of WAN failure, clients already connected can continue to connect and operate as normal.
- B. FlexConnect (H-REAP) should not be considered to manage the WLAN. In the event of WAN failure, clients already connected will be dropped and need to re-associate and re- authenticate to the network, using the in-store RADIUS and directory services.
- C. The Cisco 2504 WLC should be considered to manage the store WLANs. The Cisco 2504 WLC will provide full services to the store and can be managed and configured from a centralized controller. In the event of WAN failure, clients already connected can continue to connect and operate as normal.
- D. The Cisco 2504 WLC should be considered to manage the store WLANs. The Cisco 2504 WLC will provide full services to the store and can be managed and configured from a centralized management system (NCS or WCS). In the event of WAN failure, clients already connected can continue to connect and operate as normal.
- E. The Cisco 7510 WLC should be considered to be deployed in each store to manage the store WLAN. In the event of WAN failure, clients already connected can continue to connect and operate as normal.

Correct Answer: AD

Latest 350-050 Dumps

350-050 Practice Test

350-050 Braindumps

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.lead4pass.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © lead4pass, All Rights Reserved.