



350-080^{Q&As}

CCIE Data Center Written

Pass Cisco 350-080 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.lead4pass.com/350-080.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A virtual port channel (vPC) allows links that are physically connected to two different Cisco Nexus devices to appear as a single port channel to a third device.

Which are the mandatory steps for configuring vPC? (Choose six.)

- A. Enable feature vPC
- B. Define domains
- C. Establish peer keepalive connectivity
- D. Create a peer link
- E. Configure the peer link as a trunk port
- F. Create port channels and vPCs
- G. Define port channel load-balancing method
- H. Make sure configurations are consistent

Correct Answer: ABCDFH

QUESTION 2

Which three statements about the DHCP snooping feature on Cisco Nexus switches are true? (Choose three.)

- A. DHCP snooping commands are not available until the feature is enabled with the feature dhcp-snooping command.
- B. When you enable the DHCP snooping feature, the switch begins building and maintaining the DHCP snooping binding database.
- C. The switch will not validate DHCP messages received or use the DHCP snooping binding database to validate subsequent requests from untrusted hosts until DHCP snooping is enabled globally and for each specific VLAN.
- D. Globally disabling DHCP snooping removes all DHCP snooping configuration on the switch.
- E. Globally disabling DHCP snooping does not remove any DHCP snooping configuration or the configuration of other features that are dependent upon the DHCP snooping feature.

Correct Answer: BCE

QUESTION 3

Refer to the exhibit.



Boot Order Details

Configured Boot Order | Actual Boot Order

+ - Filter Export Print

| Name | Order | vNIC/vHBA/iSCSI vNIC | Type | Lun ID | WWN |
|--------|-------|----------------------|---------|--------|-----|
| CD-ROM | 1 | | | | |
| ISCSI | 2 | iscsiC | Primary | | |

Boot Order Details

Configured Boot Order | Actual Boot Order

There may be a delay of a few minutes before the actual boot order is updated.
Last Update: 2013-10-28T08:49:26

+ - Export Print

| Name |
|--------------------------------|
| CD/DVD |
| (1) Cisco vKVM-Mapped vDVD1.22 |
| Internal EFI Shell |

You have associated a newly created service profile to a blade. When you examine the configured boot order and actual boot order, they do not match. Which two statements describe reasons for this mismatch? (Choose two.)

- A. Having a single iSCSI boot target would prevent the profile from associating, and would generate a configuration error.
- B. The server must complete a POST cycle before Cisco UCS Manager will update this information.
- C. The blade needs to be reacknowledged.
- D. The server is in the process of a firmware upgrade.
- E. There may be a configuration error in the service profile.

Correct Answer: BE

QUESTION 4

Which two statements about Cisco Nexus 1000V Series Switches are correct? (Choose two.)



A. When VSM interfaces are created for a virtual machine, the VMware vSwitch port-group configuration is used initially, which requires the creation of a port-group name for these interfaces and an appropriate VLAN. The simplest configuration is to create a single port group (for example, VSM-Interfaces), that includes all the interfaces that use this port group and the same VLAN.

B. The mgmt0 interface on the VSM does not necessarily require its own VLAN. In fact, you can use the same VLAN to which the VMware vCenter Server belongs. The VSM management VLAN is really no different from any other virtual machine data VLAN. Alternatively, network administrators can designate a special VLAN for network device management.

C. Always deploy the Cisco Nexus 1000V Series VSM in pairs, with one VSM that is defined as the primary module and the other that is defined as the secondary module on two separate hosts.

D. The service console is a critical interface that resides on every logical server.

Correct Answer: BC

QUESTION 5

On a Cisco UCS B250 server, how many physical DIMM slots make up one logical DIMM?

A. 2

B. 3

C. 4

D. 6

E. 12

Correct Answer: A

[Latest 350-080 Dumps](#)

[350-080 Study Guide](#)

[350-080 Exam Questions](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.lead4pass.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket:



| | | |
|---|---|--|
|  <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p> |  <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p> |  <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p> |
|---|---|--|

Any charges made through this site will appear as Global Simulators Limited.
All trademarks are the property of their respective owners.
Copyright © lead4pass, All Rights Reserved.