

3V0-42.20^{Q&As}

Advanced Design VMware NSX-T Data Center

Pass VMware 3V0-42.20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/3v0-42-20.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

An architect is helping an organization with the Physical Design of an NSX-T Data Center solution.

This information was gathered during a workshop about ESXi Host networking:

A total of 50 ESXi hosts to be configured as Transport Nodes.

All ESXi hosts have a dedicated 2 × Intel 10Gbps Physical Network adapter for the Overlay Traffic.

To achieve low latency, high throughput, redundancy, and performance, which two NIC teaming policies should the architect recommend? (Choose two.)

- A. Load Balance Source MAC
- B. Load Balance Port ID
- C. Load Balance Source
- D. Load Balance Source Port ID
- E. Failover Order

Correct Answer: DE

QUESTION 2

An architect is helping an organization with the Logical Design of an NSX-T Data Center solution.

Which two statements should the architect consider as non-technical requirements? (Choose two.)

- A. Any solution should add more value to current and future customers engagements.
- B. The design should offer agility and freedom for application phases.
- C. All application servers have hardcoded IP addresses.
- D. Current business continuity and disaster recovery plans are based on tape technology.
- E. Different vendors are used for the storage solution.

Correct Answer: BD

QUESTION 3

An administrator is asked to improve Recovery Point Objective (RPO) and Recovery Time Objective (RTO) for Disaster Recovery (DR) in their company network. The network has a primary site and a secondary site. The ability to support outages with minimum loss of connectivity to the company's core application is a priority.

Which design should the administrator recommend? (Choose the best answer.)

- A. NSX-T Data Center using an Orchestrator to recover VMs across sites.
- B. NSX-T Data Center using Federation and dependencies set between primary and secondary sites.
- C. NSX-T Data Center using a registered third-party DR solution.
- D. NSX-T Data Center using built-in standard automation DR and secondary site recovery setup.

Correct Answer: B

Reference: https://docs.vmware.com/en/VMware-NSX-T-Data-Center/3.0/nsxt_30_admin.pdf

QUESTION 4

Which three IPv6 features are supported in an NSX-T Data Center design? (Choose three.)

- A. IPv6 OSPF
- B. IPv6 static routing
- C. IPv6 switch security
- D. IPv6 DNS
- E. IPv6 Distributed Firewall
- F. IPv6 VXLAN

Correct Answer: BCE

Reference: <https://blogs.vmware.com/networkvirtualization/2019/02/ipv6-support-in-nsx-t-2-4.html/>

QUESTION 5

An architect is helping an organization with the Conceptual Design of an NSX-T Data Center solution.

Which risk is documented by an architect? (Choose the best answer.)

- A. The security team has a firewall communication matrix documented.
- B. The team is not trained for NSX-T but have a very strong experience with vSphere.
- C. Open communication between different application tiers is not allowed.
- D. Aggregate N-S throughput at any given time should be at least 10G.

Correct Answer: B