VCE & PDF
Lead4Pass.com

400-151^{Q&As}

CCIE Data Center Written

Pass Cisco 400-151 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.lead4pass.com/400-151.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

According to Cisco, which two options are benefits of ITD compared to WCCP? (Choose two.)

A. does not require authentication or certificates

B. weighted load distribution

C. much less configuration

D. transparent for service node

E. requires less TCAM entries

Correct Answer: BE

QUESTION 2

Which description of Cisco Virtual Topology System is true?

A. package that contains an entire environment

B. web server hosting for Cisco NX-OS

C. overlay provisioning and management solution

D. agent that resides on physical devices

Correct Answer: C

Reference: https://www.cisco.com/c/en/us/products/cloud-systems-management/virtual-topology-system/index.html

QUESTION 3

Which statement about updating the service profile is true?

A. Updating service profile templates can have vNIC and vHBA templates that are initial templates.

B. Updating service profile templates cannot have vNIC and vHBA templates that are Initialtemplates

C. Changes made to a vNIC templat that is an Updating template are not propagated to the service profile if the service profile template is Initial.

D. Updating service profile templates can only be applied to an existing service profile.

E. Changes made to a vNIC template that is an Initial template are propagated to the service profile if the service profile template is Updating.

Correct Answer: A

QUESTION 4

Which feature is required for Dynamic ARP Inspection?

A. DIA

B. First-hop-security

C. DHCP

D. ARP

Correct Answer: C

QUESTION 5

Which two statements about NFS Appliance port failover and network uplink failure on Cisco UCS are true? (Choose two.)

A. By design, Cisco UCS fabric interconnects operate as one large fabric.

B. To change default appliance port behavior, configure an appliance port failover policy and set the action to be taken upon uplink failure.

C. By default, appliance ports are shut down ifthe uplink that they are pinned to goes down.

D. Failover cannot be configured on the Cisco UCS side for appliance ports.

E. Failover must be configures on the storage side and Cisco UCS side, and it must be implemented with the correct network design while specific failover behaviors for storage controllers are kept in mind.

Correct Answer: CD

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

https://www.lead4pass.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: