

4A0-104^{Q&As}

Alcatel-Lucent Services Architecture

Pass Alcatel-Lucent 4A0-104 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/4a0-104.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Alcatel-Lucent Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which of the following statements is NOT a valid reason to use MP-BGP as a routing protocol to transport VPRN routes?

- A. The number of VPRN routes can become very large. MP-BGP can support a very large number of routes.
- B. MP-BGP can carry routing information for a number of different address families.
- C. MP-BGP is designed to exchange information between routers that are not directly connected. This feature keeps VPRN routing information out of P-routers.
- D. MP-BGP can carry additional information attached to a route as an optional BGP attribute.
- E. All of the above statements are valid reasons for using MP-BGP as a VPRN routing protocol.

Correct Answer: E

QUESTION 2

Which of the following about transport tunnels used by services is FALSE?

- A. A transport tunnel can carry many service tunnels.
- B. The transport label is unchanged throughout the transport network.
- C. A single network port can carry more than one transport tunnel.
- D. Both MPLS and GRE transport tunnels use a service label.

Correct Answer: B

QUESTION 3

What is the default vc-type for an SDP on the Nokia 7750 SR?

- A. vc-type null
- B. vc-type ether
- C. vc-type vlan
- D. vc-type none

Correct Answer: B

QUESTION 4

What is the purpose of service mirroring on the Nokia Service Router?

- A. To mirror service requirements of a customer with a single branch office and multiple remote sites
- B. To utilize unused ports of a service router until they are required for a service.
- C. To replicate traffic from a service port to another port for debugging or monitoring functions
- D. To ease the configuration burden of services that support a large number of subscribers
- E. All of the above

Correct Answer: C

QUESTION 5

The SAP 1/1/1:2.3 receives an Ethernet frame with outer VLAN tag 5 and inner VLAN tag 3. Which of the following is TRUE?

- A. The frame is dropped.
- B. The frame's outer tag is changed to match the SAP, and it is accepted.
- C. The frame's outer tag is dropped, and the frame is accepted.
- D. The frame's tags are removed, and the frame is accepted.

Correct Answer: A

[4A0-104 VCE Dumps](#)

[4A0-104 Study Guide](#)

[4A0-104 Braindumps](#)