

4A0-107^{Q&As}

Alcatel-Lucent Quality of Service

Pass Alcatel-Lucent 4A0-107 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/4a0-107.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Alcatel-Lucent Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

On the Nokia 7750 SR, where can network-queue policies be applied? (Choose two)

- A. On the network egress port.
- B. On the SDP.
- C. On the access ingress port.
- D. On the egress MDA.
- E. On the SAP.
- F. On the ingress MDA.

Correct Answer: AF

QUESTION 2

A queue-group template can contain both queues and policers when applied under which conditions?

- A. When applied at the port level for access ingress.
- B. When applied at the FP (Forwarding Pass) level for access ingress.
- C. When applied at the FP (Forwarding Pass) level for network ingress.
- D. When applied at the port level for network egress.

Correct Answer: D

QUESTION 3

```
*A:R1>config>qos>sap-ingress# info
```

```
—— Output omitted ——
queue 5 priority-mode create
    mbs 20
    cbs 10
    high-prio-only 10
exit
queue 6 profile-mode create
    mbs 24
    cbs 24
    high-prio-only 90
exit
fc ef create
    queue 6
exit
fc "ef.in" create
    profile in
exit
fc "ef.out" create
    profile out
exit
fc l2 create
    queue 5
exit
dot1p 1 fc "l2"
dot1p 5 fc "ef.in" priority low
dscp "ef" fc "ef.out" priority high
default-fc l1
default-priority high
```

According to the SAP-ingress QoS policy shown, what is the maximum amount of memory that queue 5 can use from the shared buffer pool?

- A. 1 kilobyte
- B. 2 kilobytes
- C. 10 kilobytes
- D. 20 kilobytes

Correct Answer: D

QUESTION 4

Both SAP-ingress 10 and policer-control-policy "CFHP" have been applied to a service SAP ingress. What is the

maximum bandwidth allocated to policer 2?

```
R1>configure>qos# info
-----
---- Output omitted ----
policer-control-policy "CFHP" create
  root
    rate 100000
  exit
  tier 1
    arbiter "T1" create
      parent "root" level 4
      rate 30000
    exit
  exit
exit
sap-ingress 10 create
---- Output omitted ----
  policer 1 create
    parent "T1" level 2 weight 50
    rate 20000 cir 20000
  exit
  policer 2 create
    parent "T1" level 2 weight 50
    rate 30000 cir 10000
  exit
  policer 3 create
    parent root level 6
    rate 40000 cir 10000
  exit
  fc af create
    policer 3
  exit
  fc l2 create
    policer 2
  exit
  fc l1 create
    policer 1
  exit
  dscp "ef" fc "af"
  dotlp 3 fc "l2"
  dotlp 5 fc "l1" priority low
exit
```

- A. 10000 Kbps
- B. 15000 Kbps
- C. 20000 Kbps
- D. 30000 Kbps

Correct Answer: D

QUESTION 5

Without _____, a customer's high priority traffic can be dropped before its low priority traffic.

- A. packet filtering
- B. prioritization of traffic flows
- C. least cost routing
- D. OAM functionality
- E. separation between the data plane and the control plane

Correct Answer: B

[4A0-107 PDF Dumps](#)

[4A0-107 Exam Questions](#)

[4A0-107 Braindumps](#)