

## 4A0-C04<sup>Q&As</sup>

Nokia NRS II Composite Exam: OSPF version

### Pass Nokia 4A0-C04 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/4a0-c04.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

To enable the LDP-over-RSVP feature, which of the following configurations is NOT required on an Nokia 7750 SR?

- A. Enable the ldp-over-rsvp feature on all PEs and ABRs along the LSP tunnel.
- B. Configure Link-LDP sessions between each PE-ABR and ABR-ABR pair.
- C. Configure RSVP-TE LSPs in each area between each PE-ABR and ABR-ABR pair.
- D. Configure T-LDP sessions with the tunneling option.

Correct Answer: B

---

**QUESTION 2**

In a Layer 2 encapsulation using T-LDP, what does the second (bottom) label represent?

- A. Tunnel Label
- B. VC Label
- C. Operational Control Word
- D. VPI
- E. VCI

Correct Answer: B

---

**QUESTION 3**

Which of the following about VPN labels is FALSE?

- A. They are signaled between PE devices using MP-BGP.
- B. They are swapped at each P router as a packet crosses the service provider network.
- C. They are also known as the inner label or service label.
- D. They indicate to the egress PE the VPRN to which a packet belongs.

Correct Answer: B

---

**QUESTION 4**

What is the default Nokia 7750 SR TTL of a BGP advertisement between confederation members?

- A. 1

B. 32

C. 64

D. 255

Correct Answer: A

---

## QUESTION 5

An E-pipe is configured with a service MTU of 5000. What is the minimum MTU value that should be set on an access port for a dot1q encapsulated SAP on this service?

A. 5000

B. 5004

C. 5008

D. 5014

Correct Answer: B

[Latest 4A0-C04 Dumps](#)

[4A0-C04 PDF Dumps](#)

[4A0-C04 Study Guide](#)