

# 4A0-M10<sup>Q&As</sup>

Nokia 5G Packet Core Architecture

## Pass Nokia 4A0-M10 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/4a0-m10.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A UE has a PDU session established using slice 1. The operator removes slice 1 from the UE subscription data stored in UDM. Which of the following actions is NOT performed as a result?

- A. UDM notifies the serving AMF about the UE subscription data modification.
- B. AMF initiates the UE configuration update procedure.
- C. AMF requests the UE to release the established PDU session.
- D. UE updates its slicing information with the data received from AMF.

Correct Answer: B

---

**QUESTION 2**

A connected UE moves from 5GS to EPS using the inter-system handover procedure with N26 interface. Which of the following actions is NOT performed?

- A. Source gNB sends an NGAP Handover Required message to source AMF with handover type set to "NRtoLTE".
- B. Source AMF obtains session management contexts stored in UDM+HSS for each PDU session that supports interworking.
- C. Source AMF sends a Forward Relocation Request message to the target MME and provides session management contexts.
- D. Indirect downlink data forwarding paths are established from source gNB to target eNodeB.

Correct Answer: B

---

**QUESTION 3**

Which of the following statements about 5G QoS Flows is FALSE?

- A. A QoS Flow is the finest granularity of QoS differentiation within a PDU session.
- B. A PDU session has one or more QoS Flows.
- C. All QoS Flows of a PDU session are served by a single N3 GTP-U tunnel.
- D. Each QoS Flow is served by a dedicated data radio bearer.

Correct Answer: D

---

## QUESTION 4

Which of the following statements about the protection of service-based interfaces (SBIs) is FALSE?

- A. The transport layer security (TLS) performs certification-based authentication, providing connection security between network functions within a PLMN.
- B. The OAuth 2.0 framework is used to secure the communication between network functions within a PLMN at the network layer.
- C. The network domain security/Internet protocol (NDS/IP) provides confidentiality and data integrity between network functions within a PLMN.
- D. The security edge protection proxy (SEPP) handles the security of inter-domain SBIs and protects the interaction between network functions in different PLMNs.

Correct Answer: D

Reference: <https://www.broadforward.com/security-edge-protection-proxy/>

---

## QUESTION 5

Which of the following statements about non-access stratum mobility management (NAS-MM) protocol is TRUE?

- A. It runs between the UE and the SMF.
- B. It is used to control user plane resources between the UE and a data network.
- C. It provides common procedures such as authentication, identification, and UE configuration update.
- D. NAS-MM messages are relayed transparently by the AMF.

Correct Answer: C

[Latest 4A0-M10 Dumps](#)

[4A0-M10 Study Guide](#)

[4A0-M10 Braindumps](#)