

## 500-920<sup>Q&As</sup>

Cisco Data Center Unified Computing Infrastructure Troubleshooting  
(DCITUC)

**Pass Cisco 500-920 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/500-920.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

If a Cisco UCS B-Series server fails to initialize, which method of access is required to troubleshoot?

- A. Use direct console access to troubleshoot initialization
- B. Use Cisco UCS Manager GUI to troubleshoot initialization
- C. Use Cisco UCS Manager API to troubleshoot initialization
- D. Use KVM console to troubleshoot initialization

Correct Answer: D

---

**QUESTION 2**

What are three possible causes of service profile association failure due to iSCSI configuration issue? (Choose three )

- A. Wrong WWNN
- B. iSCSI Target out of configured range of services
- C. Inappropriate network configuration
- D. Improperly assigned iSCSI Class of Service
- E. Misconfigured iSCSI parameters
- F. Misconfigured LUN. LUN masking

Correct Answer: BCE

---

**QUESTION 3**

Which two statements describes connecting the IO Modules in the UCS chassis to the Fabric interconnects? (Choose two )

- A. Connect FI-A to the IOM B of each chassis
- B. Connect FI-B to IOM A and IOM B in each chassis
- C. Connect FI-A to the IOM A of each chassis
- D. Connect FI-A to IOM A and IOM B in each chassis
- E. Connect FI-B to the IOM A of each chassis
- F. Connect FI-B to the IOM B of each chassis

Correct Answer: ACF

---

## QUESTION 4

When configuring UCS SAN Connectivity to a 3rd Party FibreChannel Storage Array that is connecting directly to the UCS Fabric Interconnects, which option is Cisco recommended\''?

- A. Connect the Storage Array to a RC Storage Port and Enable NPV Mode on the UCS Fabric Interconnects
- B. Connect the Storage Array to an Appliance Port and Enable NPV Mode on the UCS Fabric Interconnects
- C. Direct connectivity between UCS Fabric Interconnects and FibreChannel Storage Arrays is not supported
- D. Connect the Storage Array to a FC Storage Port and Enable Switching Mode on the UCS Fabric Interconnects
- E. Connect the Storage Array to an Appliance Port and Enable Switching Mode on the UCS Fabric Interconnects

Correct Answer: D

---

## QUESTION 5

What occurs that causes a Split Brain Issue with Fabric Interconnects?

- A. The subordinate Fabric Interconnect detects heartbeat failure and declares itself primary
- B. Manage configuration changes made with UCS Manager
- C. A quorum tie occurs that must be resolved by the SEEPROM
- D. Both cluster links fail

Correct Answer: A

[500-920 PDF Dumps](#)

[500-920 Study Guide](#)

[500-920 Exam Questions](#)