

500-920^{Q&As}

Cisco Data Center Unified Computing Infrastructure Troubleshooting
(DCITUC)

Pass Cisco 500-920 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/500-920.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

When booting up a Cisco UCS Server you want to see boot time diagnostic messages of the POST, what action is required for you to do so?

- A. Enable Quiet Boot on the Server\\'s BIOS
- B. Restart the Server
- C. Disable Fast Boot on the Server\\'s BIOS
- D. Enable Quiet Boot on the Server\\'s Service Profile
- E. Disable Fast Boot on the Server\\'s Service Profile

Correct Answer: D

QUESTION 2

Which two formats can be configured for Cisco\\'s Call Home email message? (Choose two)

- A. JSON
- B. CSV
- C. Full text
- D. XML

Correct Answer: CD

<http://www.audentia-gestion.fr/cisco/smart-call-home-feature-guide-1611.pdf>

Call Home Message Formats The Call Home feature offers the following message formats:

Short Text -- Suitable for pagers or printed reports.

Plain Text -- Full formatted message information suitable for human reading.

XML -- Matching readable format using Extensible Markup Language (XML) and Adaptive Markup Language (AML) document type definitions (DTDs).

The XML format enables communication with the Cisco TAC. For user- defined destination profiles, the format options are long-text, short-text, or XML. The default is XML. For the predefined Cisco TAC profile, only XML is allowed.

QUESTION 3

Which are two Application Gateways primary roles? (Choose two) A. Manage configuration changes during FSM transitions

B. Communicate with virtual machines and report health and state

C. Automate updates to the XML Database

D. Communicate with end points and report their health and state

E. Manage configuration changes made with UCS Manager

Correct Answer: AC

QUESTION 4

Which statement is true when using SPAN for Fibre Channel (FC) Traffic?

A. FC port on Cisco UCS 6238UP can be used as a SPAN source

B. When defining FC uplink port as the SPAN destination, system will automatically stop using that port as an uplink port

C. Any port can be used as a SPAN destination port Even if it is defined as Eth uplink port it will be automatically converted to FC uplink port

D. For FC SPAN sessions we do not have to specifically enable the monitoring session

Correct Answer: A

QUESTION 5

What occurs that causes a Split Brain Issue with Fabric Interconnects?

A. The subordinate Fabric Interconnect detects heartbeat failure and declares itself primary

B. Manage configuration changes made with UCS Manager

C. A quorum tie occurs that must be resolved by the SEEPROM

D. Both cluster links fail

Correct Answer: A

[500-920 PDF Dumps](#)

[500-920 VCE Dumps](#)

[500-920 Study Guide](#)