

## 500-920<sup>Q&As</sup>

Cisco Data Center Unified Computing Infrastructure Troubleshooting  
(DCITUC)

### Pass Cisco 500-920 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/500-920.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



## QUESTION 1

After performing a UCS firmware upgrade, which two UCS components will require updated drivers? (Choose two )

- A. VIC Cards and Fiber Channel HBAs
- B. Cisco Fabric Interconnects
- C. Cisco UCS Manager
- D. RAID Controllers

Correct Answer: AB

---

## QUESTION 2

What is the result of enabling the Core File Exporter in UCS Manager?

- A. A core dump file will be immediately created and transmitted using HTTP protocol
- B. A core dump must be remotely activated by Cisco TAC.
- C. A core dump will immediately be generated and will be exported
- D. If a subsequent triggering event occurs, a core dump will be generated and sent by TFTP

Correct Answer: C

---

## QUESTION 3

The UCS Chassis Discovery Policy has been set to four and a new chassis is connected with two links What is the resulting chassis recognition action?

- A. The chassis will not be recognized
- B. The Chassis Discovery Policy will automatically reset to two links, since it always tracks the physical connections
- C. The chassis will be recognized and both links will be active
- D. The chassis will be recognized but only one of the links will be active.

Correct Answer: A

---

## QUESTION 4

Which ethernet port type is used when configuring UCS Fabric Interconnect connections to Cisco UCS C-series servers?

- A. Server Port

- B. Uplink Port
- C. Direct Connect Port
- D. Service Profile Port

Correct Answer: B

---

## QUESTION 5

You are experiencing intermittent connectivity issues on one specific Cisco UCS server. Some applications work, while others do not transfer data. You suspect jumbo frame limitations.

Which two places do you check the jumbo frame settings? (Choose two.)

- A. Check server's service profile and/or service profile template
- B. Check server's QoS System Class
- C. Check the fibre channel port configuration for jumbo frame configuration
- D. Check upstream switch ports frame size configuration
- E. Check server's individual vNICs and/or vHBAs properties

Correct Answer: BD

[500-920 Practice Test](#)

[500-920 Study Guide](#)

[500-920 Braindumps](#)