

## 500-920<sup>Q&As</sup>

Cisco Data Center Unified Computing Infrastructure Troubleshooting  
(DCITUC)

### Pass Cisco 500-920 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/500-920.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



## QUESTION 1

Which statement is true when using SPAN for Fibre Channel (FC) Traffic?

- A. FC port on Cisco UCS 6238UP can be used as a SPAN source
- B. When defining FC uplink port as the SPAN destination, system will automatically stop using that port as an uplink port
- C. Any port can be used as a SPAN destination port Even if it is defined as Eth uplink port it will be automatically converted to FC uplink port
- D. For FC SPAN sessions we do not have to specifically enable the monitoring session

Correct Answer: A

---

## QUESTION 2

When configuring UCS SAN Connectivity to a 3rd Party FibreChannel Storage Array that is connecting directly to the UCS Fabric Interconnects, which option is Cisco recommended\?

- A. Connect the Storage Array to a RC Storage Port and Enable NPV Mode on the UCS Fabric Interconnects
- B. Connect the Storage Array to an Appliance Port and Enable NPV Mode on the UCS Fabric Interconnects
- C. Direct connectivity between UCS Fabric Interconnects and FibreChannel Storage Arrays is not supported
- D. Connect the Storage Array to a FC Storage Port and Enable Switching Mode on the UCS Fabric Interconnects
- E. Connect the Storage Array to an Appliance Port and Enable Switching Mode on the UCS Fabric Interconnects

Correct Answer: D

---

## QUESTION 3

A Hard Drive (HDD) has been hot swapped in a UCS server blade, however, the UCS Manager GUI is not displaying updated metrics about the replacement drive. What action will be required to properly display updated metrics?

- A. Remove and re-insert the server blade HDD controller mezzanine card
- B. Reboot the Fabric Interconnects
- C. Reboot the server.
- D. Use the CLI, since HDD metrics cannot be displayed with the UCS Manager GUI

Correct Answer: A

---

## QUESTION 4

What is the result of enabling the Core File Exporter in UCS Manager?

- A. A core dump file will be immediately created and transmitted using HTTP protocol
- B. A core dump must be remotely activated by Cisco TAC.
- C. A core dump will immediately be generated and will be exported
- D. If a subsequent triggering event occurs, a core dump will be generated and sent by TFTP

Correct Answer: C

---

## QUESTION 5

Which command sequence is required to reset Cisco Integrated Management Controller (IMC) of a Cisco UCS Server?

- A. connect cimc | reset | validate
- B. scope cimc | reset | commit-buffer
- C. connect cimc | reset | commit
- D. scope cimc | reset | validate

Correct Answer: B

[500-920 VCE Dumps](#)

[500-920 Practice Test](#)

[500-920 Exam Questions](#)