

600-210^{Q&As}

Implementing Cisco Service Provider Mobility UMTS Networks

Pass Cisco 600-210 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/600-210.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



QUESTION 1

Which option describes how a PDN connection context is identified at the PGW?

- A. IMSI and EPS bearer ID
- B. IMSI, EPS bearer ID, and interface type
- C. IMSI, QoS, and EPS bearer ID
- D. MSISDN, QoS, and interface type

Correct Answer: B

QUESTION 2

In which two scenarios is a create bearer request sent from the SGW to the SGSN on the S4 interface? (Choose two.)

- A. secondary PDP context activation procedure
- B. network-requested secondary PDP context activation procedure
- C. network-triggered service request procedure
- D. when downlink data arrives for the released bearers
- E. PGW restart restoration procedure

Correct Answer: AB

QUESTION 3

Your company is adding additional subscriber IP network ranges and requires many-to-one NAT to be configured on the Cisco ASR 5000 for the subscriber IP network 10.11.23.0/24. The public IP range is 172.20.21.20 172.20.21.110, and each IP has no more than 100 subscribers. Which configuration option accomplishes this task?

- A. active-charging service ACS_ACME access-ruledef apn_cisco ip src-address = 10.11.23.0/24 fw-and-nat policy base_1 access-rule priority 1 access-ruledef apn_cisco permit nat-realm nat_pool1 nat policy nat-required default-nat-realm nat_pool1 rulebase acme_rulebase fw-and-nat default-policy base_1 context cisco ip pool nat_pool1 range 172.20.21.20 172.20.21.110 napt-users-per-ip-address 100
- B. active-charging service ACS_ACME access-ruledef apn_cisco ip src-address = 10.11.0.0/16 fw-and-nat policy base_1 access-rule priority 1 access-ruledef apn_cisco permit nat-realm nat_pool1 nat policy nat-required default-nat-realm nat_pool1 rulebase acme_rulebase fw-and-nat default-policy base_1 context cisco ip pool nat_pool1 range 172.20.21.20 172.20.21.110 napt-users-per-ip-address 1000
- C. active-charging service ACS_ACME access-ruledef apn_cisco ip src-address = 10.11.23.0/24 nat-and-pat policy

nat_1 access-rule priority 1 access-ruledef apn_cisco permit nat-realm nat_pool1 nat policy nat-required default-nat-realm nat_pool1 context cisco ip pool nat_pool1 range 172.20.21.20 172.20.21.29 napt-users-per-ip-address 100

D. active-charging service ACS_ACME access-ruledef apn_cisco ip src-address = 10.11.23.0/24 fw-and-nat policy base_1 access-rule priority 1 access-ruledef apn_cisco permit nat-realm nat_pool1 nat policy nat-required default-nat-realm nat_pool1 rulebase acme_rulebase fw-and-nat default-policy base_1 context cisco ip pool nat_pool1 range 172.20.21.20 172.20.21.29 napt-users-per-ip-address 100

Correct Answer: A

QUESTION 4

Which two nodes implement the GTP-U protocol in a UMTS network? (Choose two.)

- A. Gateway GPRS Support Node
- B. Base Station Controller
- C. Radio Network Controller
- D. Home Location Registrar
- E. Mobility Management Entity
- F. Mobile Switching Center

Correct Answer: AB

QUESTION 5

Which option lists the contents of the flow label in a GTPv0 header?

- A. IMSI and NSAPI
- B. MSISDN and NSAPI
- C. IMEI and NSAPI
- D. IMSI and Transaction Identifier
- E. IMEI and Transaction Identifier

Correct Answer: A
