

600-210^{Q&As}

Implementing Cisco Service Provider Mobility UMTS Networks

Pass Cisco 600-210 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/600-210.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Drag and arrange the steps on the left in the correct order on the right that indicates how DPC+ SSN based routing in SGSN is performed on the Cisco ASR 5000.

SS7 routing domain from the SCCP network is picked and point code in the SS7 RD is available	First
SCCP network in the map-service	Second
SSN service state is in-service in the SCCP network	Third
DPC in the SCCP network is accessible	Fourth

Select and Place:

Drag and arrange the steps on the left in the correct order on the right that indicates how DPC+ SSN based routing in SGSN is performed on the Cisco ASR 5000.

SS7 routing domain from the SCCP network is picked and point code in the SS7 RD is available	First
SCCP network in the map-service	Second
SSN service state is in-service in the SCCP network	Third
DPC in the SCCP network is accessible	Fourth

Correct Answer:

Drag and arrange the steps on the left in the correct order on the right that indicates how DPC+ SSN based routing in SGSN is performed on the Cisco ASR 5000.

	SCCP network in the map service
	SS7 routing domain from the SCCP network is picked and point code in the SS7 RD is available
	DPC in the SCCP network is accessible
	SSN service state is in-service in the SCCP network

QUESTION 2

In which two ways does SGSN detect and know when GGSN has restarted? (Choose two.)

- A. change in recovery value in echo response
- B. change in recovery value in PDU notification request from GGSN to SGSN

- C. change in recovery value in Update PDP Context Request from GGSN to SGSN
- D. when the sequence number in a response message is different from that of the request message
- E. when the TEID value in response in GTP header is different from that of the request message

Correct Answer: AC

QUESTION 3

Which failure code is sent in the authentication reject message when a UE with USIM fails to receive the AUTN as part of the authentication and ciphering request from the SGSN?

- A. GSM authentication unacceptable
- B. MAC failure
- C. SYNC failure
- D. RAND failure
- E. UMTS authentication unacceptable

Correct Answer: A

QUESTION 4

Refer to the exhibit.

```
charging-action cg-1
  content-id 100
  cca charging-credit

ruledef icmp-any
  icmp any-match = true

rulebase rulebase-1
  action priority 100 ruledef icmp-any charging-action cg-1

credit-control group test
  diameter endpoint gy-1
  diameter send-ccri traffic-start
```

Which three Diameter AVPs are sent within the CCR-I request to the OCS? (Choose three.)

- A. Session-ID

- B. Used-Service-Unit
- C. Request-Service-Unit
- D. 3GPP-Quota-Consumption-Time
- E. Subscription-ID
- F. Event-Trigger

Correct Answer: ACE

QUESTION 5

Which option describes the advantage of using L2TP over IPsec versus IPsec only?

- A. L2TP improves performance.
- B. The overhead that is introduced is lower.
- C. L2TP can transport protocols other than IP.
- D. L2TP provides Layer 2 VPN functionality.

Correct Answer: C

[Latest 600-210 Dumps](#)

[600-210 PDF Dumps](#)

[600-210 Exam Questions](#)