

600-511^{Q&As}

Designing with Cisco Network Programmability for ACI

Pass Cisco 600-511 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.leads4pass.com/600-511.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

When building a contract, what is the function of a filter?

- A. classification of traffic
- B. a Layer 7 parameter setting for filtering application calls
- C. to drop or adjust routing updates
- D. to enforce SLAs

Correct Answer: A

QUESTION 2

When designing an ACI fabric for a VMWare environment, which two options are supported vSwitch options? (Choose two.)

- A. external switch
- B. AVS
- C. standard vswitch
- D. DVS
- E. ESXi

Correct Answer: BD

QUESTION 3

Which two statements about server connectivity in ACI are true? (Choose two.)

- A. Unicast traffic from servers in the same EPG is not permitted unless a specific contract allows it.
- B. Unicast traffic from servers in a different EPG is not permitted unless a specific contract allows it.
- C. Unicast traffic from servers in a different EPG is not permitted unless both EPGs are in the same bridge domain.
- D. Multicast traffic from servers in the same EPG is not permitted unless a specific contract allows it.
- E. Multicast traffic from servers in the different EPG is not permitted unless a specific contract allows it.
- F. Multicast traffic from servers in a different EPG is not permitted unless both EPGs are in the same bridge domain.

Correct Answer: BF



https://www.leads4pass.com/600-511.html

2024 Latest leads4pass 600-511 PDF and VCE dumps Download

QUESTION 4

Which option is for migrating an existing Data Center network to Cisco ACI?

- A. First migrate existing FEXs to 9500.
- B. First connect the core (for example, Cisco ASR 9000 Router or Cisco Nexus 7000 Series Switches) to the ACI fabric that supports external connectivity routing mechanisms (OSPF NSSA, iBGP, and static routes).
- C. First disable flooding on each bridge domain during migration to avoid broadcast storms.
- D. First migrate existing access layer (for example, Catalyst 5500/6000 + FEX) to Cisco MDS 9500 Series.

Correct Answer: B

QUESTION 5

Which two options are two intended uses of Layer 3-External in the ACI fabric? (Choose two.)

- A. to provide connectivity to external networks
- B. to advertise a default gateway into the ACI fabric
- C. to define the default gateway for the devices connected to the ACI fabric
- D. to advertise IP and MAC information outside of the ACI fabric
- E. to apply policy to endpoints not contained in an EPG

Correct Answer: AB

600-511 VCE Dumps

600-511 Practice Test

600-511 Exam Questions