

98-388^{Q&As}

Introduction to Programming Using Java

Pass Microsoft 98-388 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/98-388.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Microsoft
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

DRAG DROP

You have a Java class named InsurancePolicy.

You need to define a constant data member named RATE. The data member must be accessible by any class without instantiating the InsurancePolicy class.

How should you complete the code? To answer, drag the appropriate code segment to the correct position. Each code segment may be used once, more than once, or not at all. You may need to drag the split bar between panes or scroll to

view content.

NOTE: Each correct selection is worth one point.

Select and Place:

Code Segments

final	finally
private	protected
public	static
super	void

Answer Area

```
public class InsurancePolicy
{
    [ ] [ ] [ ] double RATE = .0642;
}
```

Correct Answer:

Code Segments

	finally
private	protected
super	void

Answer Area

```
public class InsurancePolicy
{
    public static final double RATE = .0642;
}
```

References: <https://docs.oracle.com/javase/tutorial/java/javaOO/classvars.html>

QUESTION 2

DRAG DROP

You are interviewing for a job at Adventure Works, Inc. The hiring manager asks you to create a single console program.

The program takes multiple arguments from the command line and writes them to the screen in the same order as they were typed on the command line.

Which three code segments should you use to develop the solution? To answer, move the appropriate code segments from the list of code segments to the answer area and arrange them in the correct order.

Select and Place:

Code Segments

```
public static void main(String arguments) {  
  
    for (int i = 0; i < args.length; i++) {  
  
        System.out.println(args[i]);  
    }  
}  
  
for (int i = 1; i <= Integer.parseInt(args[0]); i++) {  
  
    System.out.println(arguments[i]);  
}  
}  
  
public static void main(String[] args) {  
  
    for (int i = 0; i < arguments.length; i++) {
```



Answer Area

Correct Answer:

Code Segments

```
public static void main(String arguments) {  
  
    for (int i = 0; i < args.length; i++) {  
  
        System.out.println(args[i]);  
    }  
}  
  
for (int i = 1; i <= Integer.parseInt(args[0]); i++) {  
  
    System.out.println(arguments[i]);  
}  
}
```



Answer Area

```
public static void main(String[] args) {  
  
    for (int i = 0; i < arguments.length; i++) {  
  
        System.out.println(arguments[i]);  
    }  
}
```

QUESTION 3

HOTSPOT

You need to evaluate the following code. Line numbers are included for reference only.

```

01 public static int fee(char model) {
02     int price = 0;
03     switch (model) {
04         case 'A':
05             price = 50;
06             break;
07         case 'T':
08             price = 20;
09         case 'C':
10             price = 5;
11             break;
12         default:
13             price = 100;
14             break;
15     }
16     return price;
17 }

```

Use the drop-down menus to select the answer choice that answers each question based on the information presented in the code. NOTE: Each correct selection is worth one point.

Hot Area:

Answer Area

What is the return value when `model` has a value of 'A'?

▼
5
20
50
100

What is the return value when `model` has a value of 'T'?

▼
5
20
50
100

What is the return value when `model` has a value of 'c'?

▼
5
20
50
100

What is the return value when `model` has any other value?

▼
5
20
50
100

Correct Answer:

Answer Area

What is the return value when `mode1` has a value of 'A'?

	▼
5	
20	
50	
100	

What is the return value when `mode1` has a value of 'T'?

	▼
5	
20	
50	
100	

What is the return value when `mode1` has a value of 'c'?

	▼
5	
20	
50	
100	

What is the return value when `mode1` has any other value?

	▼
5	
20	
50	
100	

QUESTION 4

You need to evaluate the following code segment:

```
double dNum = 2.667;  
int iNum = 0;  
iNum = (int)dNum;
```

What happens when the code segment is run?

- A. `iNum` has a value of 0.
- B. An exception is thrown.
- C. `iNum` has a value of 2.
- D. `iNum` has a value of 3.

Correct Answer: C

QUESTION 5

HOTSPOT

You are creating a method that converts a string representation of a number into an actual number.

The numbers passed into the method include whole numbers and fractional numbers.

How should you complete the code? To answer, select the appropriate code segments in the answer area.

NOTE: Each correct selection is worth one point.

Hot Area:

Answer Area

```
public void convertStringToNumber(String numberAsString)
{
    [dropdown] number = [dropdown] . [dropdown] (numberAsString);

    System.out.println(number);
}
```

▼
double
Integer
String

Double
double
Integer
String

▼
format
parseDouble
parseInt

Correct Answer:

Answer Area

```
public void convertStringToNumber(String numberAsString)
{
    [dropdown] number = [dropdown] . [dropdown] (numberAsString);

    System.out.println(number);
}
```

▼
double
Integer
String

Double
double
Integer
String

▼
format
parseDouble
parseInt

References: <https://docs.oracle.com/javase/tutorial/java/data/converting.html>