ACE-A1.2^{Q&As}

Arista Certified Engineering Associate

Pass Arista ACE-A1.2 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.leads4pass.com/ace-a1-2.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Arista Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

😳 365 Days Free Update

Leads4Pass

800,000+ Satisfied Customers



Leads4Pass

QUESTION 1

What service does the MLAG feature provide?

- A. Layer 3 OSPF redundancy
- B. Telco redundancy
- C. Layer 2 redundancy and increased Layer 2 bandwidth
- D. Access List group therapy

Correct Answer: C

QUESTION 2

What is the EOS command that allows Arista switches with Multi-switch CLI enabled to send interactive commands to multiple switches at once?

- A. xmpp group
- B. xmpp send switch-group
- C. xmpp session
- D. xmpp session-name
- Correct Answer: C

Reference: https://www.arista.com/en/um-eos-4172f/eos-section-2-5-session-management-commands

QUESTION 3

Which of the following statements is false?

- A. You can run bash commands from CLI with the bash command.
- B. You can run CLI commands from bash with the Cli command.
- C. You can run CLI commands from bash with the FastCli command.
- D. You can run CLI commands from CLI with the Cli command.

Correct Answer: D

QUESTION 4

Which command will disable Adaptive Segmentation in VMTracer?

Leads4Pass

- A. Student-01(config-vmtracer-session)#autovlan disable
- B. Student-01(config-vmtracer-session)#no autovlan
- C. Student-01(config-vmtracer-session)#no autovlan enable
- D. Adaptive Segmentation cannot be disabled in VMTracer

Correct Answer: A

Reference: https://www.arista.com/assets/data/pdf/user-manual/um-eos-4172f/Chapters/um-eos4172f_VM%20Tracer.pdf (page 4)

QUESTION 5

When configuring MLAG, Arista recommends that the trunk group command be used on the VLAN used for MLAG peer communication.

What is the purpose of the trunk group command?

- A. It groups all the trunks together so that they can traverse the peer-link properly.
- B. It groups the MLAG interfaces together so that they can be reported on both peers.
- C. It prevents the configured VLAN from leaking out onto other trunks.
- D. It ensures that the configured VLAN will be included on all trunks.

Correct Answer: A

ACE-A1.2 PDF Dumps

ACE-A1.2 Practice Test

ACE-A1.2 Study Guide