

ACMA_6.3^{Q&As}

Aruba Certified Mobility Associate 6.3

Pass HP ACMA_6.3 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.leads4pass.com/acma_6-3.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which one of the following file types cannot be imported to Visual RF Plan?

- A. dwg
- B. jpg
- C. tiff
- D. gif
- E. bmp

Correct Answer: C

QUESTION 2

Aliases are used in firewall policies to:

- A. Apply firewall policies to ports in a stateful manner
- B. Make firewall rules act like traditional ACLs
- C. Ease readability and maintainability for source and destination addresses
- D. Are a part of roles, not the firewall
- E. Are applied as an action in a rule

Correct Answer: C

QUESTION 3

Which of the following statements about management accounts is false?

- A. The root account can be used to monitor access points connected to the controller
- B. The guest-provisioning account can see the controller's configuration but cannot change it
- C. The read-only account cannot delete internal database entries
- D. The guest-provisioning account can make changes to the internal AP database
- E. The network-operations account cannot access configuration

Correct Answer: B

QUESTION 4

The Guest Provisioning user account has the ability to do which of the following?

- A. Add a new employee to the internal database
- B. Change the "look" and "feel" of the guest provisioning page
- C. Change the available data fields on the guest provisioning page
- D. Add a guest user to the internal database
- E. Assign a Role to a guest account

Correct Answer: D

QUESTION 5

Which of the following is true of an Aruba Mobility Controller acting as a layer 2 switch? (Select two):

- A. The Mobility Controller is the client's default router.
- B. The Mobility Controller acts as a bridge.
- C. All stations must use the same VLAN
- D. Uplink ports on the Mobility Controller can use 802.1q tagging
- E. VLANs cannot have IP addresses

Correct Answer: BD

[Latest ACMA_6.3 Dumps](#)

[ACMA_6.3 Study Guide](#)

[ACMA_6.3 Exam Questions](#)