

ACMP_6.4^{Q&As}

Aruba Certified Mobility Professional 6.4

Pass Aruba ACMP_6.4 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.leads4pass.com/acmp_6-4.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Aruba
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

The corporation has deployed hundreds of RAP3 and all are working. A user has received a RAP3 from the IT department. At his home he connects the Ethernet port to his DSL modem. The corporate SSID is not advertised but an Instant SSID is. What could be the problem?

- A. This RAP was purchased as an IAP and not as a RAP
- B. The activate server does not have this RAPs configured
- C. The corporate Firewall is blocking VPN
- D. The RAP3 must be pre-staged
- E. The user must connect his laptop, get the Zero touch window and enter the URL

Correct Answer: B

QUESTION 2

Virtual AP > R5-employee1-vap_prof

Show Reference

Save As

Reset

Virtual AP enable	<input checked="" type="checkbox"/>	Allowed band	all ▾
VLAN	11 <-- --NONE-- ▾	Forward mode	tunnel ▾
Deny time range	--NONE-- ▾	Mobile IP	<input checked="" type="checkbox"/>
HA Discovery on-association	<input type="checkbox"/>	DoS Prevention	<input type="checkbox"/>
Station Blacklisting	<input checked="" type="checkbox"/>	Blacklist Time	3600 sec
Dynamic Multicast Optimization (DMO)	<input type="checkbox"/>	Dynamic Multicast Optimization (DMO) Threshold	6
Authentication Failure Black list Time	3600 sec	Strict Compliance	<input type="checkbox"/>
VLAN Mobility	<input type="checkbox"/>	Preserve Client VLAN	<input type="checkbox"/>
Remote-AP Operation	standard ▾	Drop Broadcast and Multicast	<input type="checkbox"/>
Convert Broadcast ARP requests to unicast	<input checked="" type="checkbox"/>	Disable conversion multicast RA packets to unicast	<input type="checkbox"/>
Deny inter user traffic	<input type="checkbox"/>	Band Steering	<input type="checkbox"/>
Steering Mode	prefer-5ghz ▾		

In the above screen capture, the administrator notes that most of the configuration options are grayed out

and have no action.

What is the cause of the problem?

- A. attempting to make global changes on a Master Controller
- B. attempting to make global changes on a Local Controller
- C. this change can only be performed via the CLI
- D. does not have the correct software license
- E. there is an error in the configuration

Correct Answer: B

QUESTION 3

Which actions does ARM (Adaptive Radio Management) perform? (Choose two)

- A. allows controllers to provision the AP Radio type
- B. allows controllers to provision the best channel for APs
- C. allows controllers to provision the best power setting for APs
- D. allows controllers to provision allowed Radio bands
- E. allows controllers to provision lower power when unauthorized APs are detected

Correct Answer: BC

QUESTION 4

Captive Portal Authentication Profile > default

Show Reference

Save As

Reset

Default Role	guest
Default Guest Role	guest
Redirect Pause	10 sec
User Login	<input checked="" type="checkbox"/>
Guest Login	<input type="checkbox"/>
Logout popup window	<input checked="" type="checkbox"/>
Use HTTP for authentication	<input type="checkbox"/>
Logon wait minimum wait	5 sec
Logon wait maximum wait	10 sec
logon wait CPU utilization threshold	60 %
Max Authentication failures	0
Show FQDN	<input type="checkbox"/>
Authentication Protocol	PAP
Login page	/auth/index.html
Welcome page	/auth/welcome.html
Show Welcome Page	<input checked="" type="checkbox"/>
Add switch IP address in the redirection URL	<input type="checkbox"/>
Adding user vlan in redirection URL	<input type="checkbox"/>
Add a controller interface in the redirection URL	address <input type="text"/>
Allow only one active user session	<input type="checkbox"/>

A user logged in with the Captive Portal settings shown in the above screen capture. What does the user need to do to logout?

- A. wait 30 minutes then logout
- B. wait 60 minutes then logout
- C. click Logout on the browser screen
- D. he cannot logout
- E. wait 10 seconds for redirect

Correct Answer: C

QUESTION 5

A client attaches to a secure jack interface set to untrusted. But when the client tries to access the captive portal page, the following message appears, "Web Authentication is not enabled." What might be wrong?

- A. The client has the browser provisioned with proxy settings.
- B. The controller port needs to be set to trusted.
- C. A "aaa" profile needs to be selected on the Wired Access page.
- D. A Captive Portal profile needs to be assigned to the initial role.
- E. Web Authentication cannot be used in this way.

Correct Answer: D

[ACMP_6.4 PDF Dumps](#)

[ACMP_6.4 VCE Dumps](#)

[ACMP_6.4 Braindumps](#)