

BH0-007^{Q&As}

ISEB Intermediate Certificate in Software Testing

Pass ISEB BH0-007 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/bh0-007.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by ISEB
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which one of the following test tools would you recommend for the E2E phase.

- A. A configuration management tool to ensure that all user-stories have been properly archived.
- B. A test design tool to create the test cases as efficiently as possible.
- C. A performance test tool to check that anticipated loading can be handled.
- D. A modelling tool to verify the stock exchange pricing structures.

Correct Answer: C

QUESTION 2

Which of the following methods of test estimation would be most appropriate for each Sprint?

- A. Ask the testers to talk to each other and reach a consensus.
- B. Take 30% of the total development time required for the Sprint.
- C. Conduct a test point analysis on the content and navigation requirements.
- D. Use metrics from the last accessibility project at MSC.

Correct Answer: A

QUESTION 3

Which of the following provides the best example of a product risk leading to a project risk?

- A. The signalling systems may have more defects than anticipated, leading to the need for more retesting to be carried out.
- B. There may be unexpected lags on the network traffic communication, causing drivers to slow the trains down unnecessarily.
- C. The new development staff may require training for this type of system, which, if not carried out, may lead to an increase in the number of defects introduced.
- D. The budget may need to be increased significantly during the project, otherwise there may be delays in the delivery of the system.

Correct Answer: A

QUESTION 4

When a software defect in a system has been found and fixed, which of the following activities should be undertaken

next?

a.

Debugging.

b.

Confirmation testing.

c.

Regression testing.

d.

System testing.

e.

Static testing.

A.

a and b.

B.

b and c.

C.

c and d.

D.

c and e.

Correct Answer: B Case Study# 4Scenario

A bank is upgrading its systems to include an on-line investment service, allowing investors to trade with each other, in a mini-stock market environment.

The upgrade will be carried out using Agile development (within the Scrum framework). Here, the iterations are referred to as Sprints. For each Sprint the required functionality will be defined as a set of user-stories.

The user stories are typically 1-2 lines long, indicating what the business wants the system to do. These user stories will be built then tested.

There will be 3 Sprints:

1) Creation of the mini-stock market trading environment.

2) Creation of additional front-end enhancements.

3) Linking to stock exchange for pricing.

You are the test manager. You lead a team of 4 testers, and there are 6 developers. Your team has worked on Agile projects previously, and on average, Sprints usually last 4 weeks. At the end of all Sprints, a full end to end test is carried out. This is called the E2E test phase. You are worried that 4 weeks will not be sufficient time for the first Sprint. You have decided to conduct a Risk Management exercise before the project starts.

QUESTION 5

Which of the following is the main purpose of an incident tracking process?

- A. To identify the average number of steps required to recreate each incident.
- B. To calculate the average turnaround times per defect.
- C. To identify the priority of each incident.
- D. To understand the status of each incident at any given time.

Correct Answer: D

Case Study # 3

Scenario

Data is transmitted over the internet as a series of packets. Each packet is sent to its destination via the best available route. The decision on the best available route is made by a series of routers on the internet.

In order to make the best decision on the route to take, the router:

1) Scans the destination address and matches it against rules set up in a configuration table. 2) Checks the performance of the primary connection to see if it is good enough to send the packet. If not,

it seeks an alternative.

Routers handle many millions of packets being sent at the same time. Packets can take the form of email

messages, data files etc.

[BH0-007 PDF Dumps](#)

[BH0-007 Study Guide](#)

[BH0-007 Exam Questions](#)