

## C4090-454<sup>Q&As</sup>

IBM High-End Tape Technical Solutions V7

**Pass IBM C4090-454 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/c4090-454.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A proposed design includes a TS7700 and one 3952 frame with three installed 3592- 007 tape controllers. What is needed to provide high availability library management for the native tape drives in the TS3500?

- A. Logical library option P04444 in the first two 007s
- B. Logical library option P04444 in the first three 007s for n-i availability
- C. No additional library management features required in the 007 as the function is provided in TS7700
- D. Logical library option P04444 in the first three 007s which also provides library management for the TS7700

Correct Answer: A

---

**QUESTION 2**

A banking customer's TS7740 was unable to replicate the tape backup data to the DR data center via the current grid network. The IBM support engineer had created a PMR with Severity 1 because the tape library is supporting the customer's production environment. Six hours after the PMR was created, IBM Level 2 support requested to change the Severity Level to 2, even though the problem had not been resolved. Based on IBM guidelines, why would this problem need to be reduced to Severity 2?

- A. Severity 1 only applies to Tape Failure
- B. Severity 1 only applies to Network Failure
- C. Severity 1 only applies to Production Failure
- D. Severity 1 problem must be resolved within 6 hours

Correct Answer: C

---

**QUESTION 3**

What is limited by Performance Increments in the TS7700?

- A. Host Read only
- B. Host Write only
- C. Host Read and Write
- D. Host Read, Write and Grid Replication

Correct Answer: B

---

## QUESTION 4

What is the maximum number of 3490 control units that can be defined in HOD for a TS7700?

- A. 16
- B. 32
- C. 64
- D. 256

Correct Answer: A

---

## QUESTION 5

What is the maximum distance between z/OS host and a TS7700 Virtualization Engine for a shortwave FICON adapter connected with 50 micron multimode at 4 Gbps?

- A. 55 m
- B. 150 m
- C. 50 Cm
- D. 10 km

Correct Answer: B

[C4090-454 VCE Dumps](#)

[C4090-454 Exam Questions](#)

[C4090-454 Braindumps](#)