C_SECAUTH_20^{Q&As}

SAP Certified Technology Associate - SAP System Security and Authorizations

Pass SAP C_SECAUTH_20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.leads4pass.com/c_secauth_20.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by SAP Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

Which of the following are core principles of GDPR? (Choose three.)

A. Data Archiving

B. Lawfulnaess, Fairness and Transparency

C. Storage Limitations

D. Data Quality

E. Data Minimization

Correct Answer: BCE

QUESTION 2

Which of the following objects allows you to restrict which users can distribute a role to another system using an RFC destination?

A. S_USER_AGR

B. S_USER_SYS

C. S_USER_STA

D. S_USER_AUT

Correct Answer: B

QUESTION 3

You want to adjust check indicator values for certain authorization objects delivered by SAP. In which of the following tables should your adjustments be recorded?

A. USOBHASH

B. USOBX

C. USOBT_C

D. USOBX_C

Correct Answer: D

QUESTION 4

In the case of missing OData authorizations, why is it not recommended to maintain S_SERVICE manually within an

SAP Fiori authorization role? (Choose two.)

A. Both front-end and back-end entries are generating the same S_SERVICE authorization object with different authorization values.

B. Both front-end and back-end entries are generating the same S_SERVICE authorization object with the same authorization values.

C. The SRV_NAME value of the S_SERVICE authorization object is the name of an OData service.

D. The SRV_NAME value of the S_SERVICE authorization object is the hash value of an OData service.

Correct Answer: AD

QUESTION 5

Where can you enable the Read Access Logging tools?

A. SWI5

B. SUIM

C. SPRO

D. SICF

Correct Answer: D

[C_SECAUTH_20 PDF Dumps](#)

[C_SECAUTH_20 Study Guide](#)

[C_SECAUTH_20 Braindumps](#)