

CWNA-106^{Q&As}

Certified Wireless Network Administrator

Pass CWNP CWNA-106 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/cwna-106.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

You are being interviewed by ABC Company for employment as a wireless site survey expert. The interviewing manager asks you what items should be included in a site survey report generated as part of a manual site survey process.

What answer would be accurate?

- A. Itemized list of equipment, licenses, and support contracts required for the facility
- B. RF heat map illustrating coverage and signal quality for each frequency band
- C. Documentation proving proper entry of wall material types into the site survey software
- D. Documentation noting how each WLAN user group will authenticate to the network

Correct Answer: B

QUESTION 2

What is a common feature of an 802.11 WLAN client utility? (Choose 2)

- A. Real-time retry monitor
- B. AP Signal strength meter
- C. Spectrum analyzer utility
- D. VLAN configuration
- E. Link statistics display

Correct Answer: BE

QUESTION 3

You are the network administrator for ABC Company. Your manager has recently attended a wireless security seminar. The seminar speaker taught that a wireless network could be hidden from potential intruders if you disabled the broadcasting of the SSID in Beacons and configured the access points not to respond to Probe Request frames that have a null SSID field.

Your manager suggests implementing these security practices. What response should you give to this suggestion? (Choose 2)

- A. Any 802.11 protocol analyzer can see the SSID in clear text in frames other than Beacons and Probe Response frames. This negates any security benefit of trying to hide the SSID in Beacons and Probe Response frames.
- B. This security practice prevents manufacturers' client utilities from detecting the SSID. As a result, the SSID cannot be obtained by attackers, except through social engineering, guessing, or use of a WIPS.
- C. Although it does not benefit the security posture, hiding the SSID in Beacons and Probe Response frames can be helpful for preventing some users (such as guests) from attempting to connect to the corporate network.

D. Any tenants in the same building using advanced penetration testing tools will be able to obtain the SSID by exploiting WPA EAPOL-Key exchanges. This poses an additional risk of exposing the WPA key.

E. To improve security by hiding the SSID, the AP and client stations must both be configured to remove the SSID from association request and response frames. Most WLAN products support this.

Correct Answer: AC

QUESTION 4

The IEEE 802.11-2012 standard requires VHT capable devices to be backward compatible with devices using which other 802.11 physical layer specification (PHY)?

- A. OFDM
- B. HR/DSSS
- C. ERP-PBCC
- D. DSSS

Correct Answer: A

QUESTION 5

What are two channel modes specified by the 802.11n (High Throughput) PHY? (Choose 2)

- A. 20 MHz
- B. 20/40 MHz
- C. 40/80 MHz
- D. 22 MHz
- E. 80 MHz
- F. 160 MHz

Correct Answer: AB

[Latest CWNA-106 Dumps](#)

[CWNA-106 PDF Dumps](#)

[CWNA-106 Exam Questions](#)