

# CWNA-107<sup>Q&As</sup>

Certified Wireless Network Administrator

**Pass CWNP CWNA-107 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/cwna-107.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

What 802.11 network configuration would result in multiple stations broadcasting Beacon frames with the same BSSID but with different source addresses?

- A. A single AP supports multiple BSSs with different SSIDs.
- B. An SCA network is in use.
- C. Multiple APs have been loaded with the same configuration from an image file.
- D. An IBSS is used instead of a BSS.

Correct Answer: D

Reference <https://www.safaribooksonline.com/library/view/80211-wireless-networks/0596100523/ch04.html>

---

## QUESTION 2

You recently purchased four laptops containing dual-band 802.11ac adapters. The laptops can connect to your 2.4 GHz network, but they cannot connect to the 5 GHz network. The laptops do not show the 5 GHz SSIDs, which are different than the 2.4 GHz SSIDs. Existing devices can connect to the 5 GHz SSIDs with no difficulty. What is the likely problem?

- A. Interference from non-Wi-Fi sources
- B. Faulty drivers
- C. DoS attack
- D. Interference from other WLANs

Correct Answer: D

---

## QUESTION 3

Which one of the following is not a factor considered when calculating the Link Budget for an outdoor point-to-point WLAN bridge link?

- A. MU-MIMO capabilities of the bridges
- B. Receive antenna gain
- C. Transmit power
- D. Operating frequency

Correct Answer: A

---

## QUESTION 4

A natural disaster has occurred in a remote area that is approximately 40 miles from the response team headquarters. The response team must setup a local wireless network using 802.11 WLAN access points. What is the best method, of those listed, for implementation of a network backhaul for communications across the Internet in this scenario?

- A. Temporary wired cable
- B. 802.11 bridging
- C. Cellular/LTE
- D. Temporary wired DSL

Correct Answer: C

---

## QUESTION 5

You are troubleshooting a controller-based AP that is unable to locate the controller. DHCP is not use and the controller is located at 10.10.10.81/24 while the AP is on the 10.10.16.0/24 network. What should be inspected to verify proper configuration?

- A. NTP
- B. BOOTH
- C. DNS
- D. AP hosts file

Correct Answer: C

[CWNA-107 PDF Dumps](#)

[CWNA-107 VCE Dumps](#)

[CWNA-107 Practice Test](#)