

# CWNA-107<sup>Q&As</sup>

Certified Wireless Network Administrator

**Pass CWNP CWNA-107 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/cwna-107.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

What non-standard WLAN solution attempts to give a longer transmission windows to devices with higher data rates then devise with lower data rates?

- A. AirTime Fairness
- B. Band Steering
- C. ARM
- D. RRM

Correct Answer: A

---

## QUESTION 2

Return Loss is the decrease of forward energy in a system when some of the power is being reflected back toward the transmitter.

What will cause high return loss in an RF transmission system, including the radio, cables, connectors and antenna?

- A. The use of cables longer than one meter in the RF system
- B. High output power at the transmitter and use of a low-gain antenna
- C. A Voltage Standing Wave Ratio (VSWR) of 1:1
- D. An impedance mismatch between components in the RF system

Correct Answer: D

---

## QUESTION 3

What factor is likely to cause the least impact on the application layer throughput of an 802.11n client station in a 2.4 GHz HT BSS?

- A. Increasing or decreasing the number of spatial streams in use by the client station and AP
- B. Implementation of several other clients in the same BSS using 802.11 g radios
- C. Implementing Fast BSS Transition (FT) for roaming
- D. RF interface from more than 10 nearby Bluetooth transmitters

Correct Answer: A

---

## QUESTION 4

A dual-band 802.11ac AP must be powered by PoE. As a class 4 device, what power level should be received at the AP?

- A. 30 W
- B. 25.5 W
- C. 15.4 W
- D. 12.95 W

Correct Answer: C

---

## QUESTION 5

When performing a validation survey for a Multiple Channel Architecture (MCA) system in a multi-tenant building with five floors, what aspect should you, as the surveyor, keep in mind?

- A. The RF interference caused by passing airplanes supporting on-board Wi-Fi should be a prime consideration
- B. The channel reuse pattern should be three dimensional with the RF cell extending coverage of each access point to other floors
- C. The omni-directional antennas of the access points should be oriented parallel to the floor to maximize the coverage pattern across as many floors as possible
- D. The Fresnel Zone is completely blocked between floors so each floor is considered a separate site survey

Correct Answer: B

[Latest CWNA-107 Dumps](#)

[CWNA-107 VCE Dumps](#)

[CWNA-107 Braindumps](#)