

# DCPPE-200<sup>Q&As</sup>

Dell PowerEdge Professional Exam

## Pass Dell DCPPE-200 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/dcppe-200.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Dell Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

An engineer needs to replicate BIOS and NIC settings for server nodes installed in the chassis. Which CMC feature should an engineer use to perform this task?

- A. AutoConfiguration
- B. Chassis Profiles
- C. QuickDeploy
- D. Server Profiles

Correct Answer: C

---

**QUESTION 2**

A password to the CMC root account on an M1000e server chassis has been misplaced. What should be done to restore administrative access to the CMC?

- A. Reset root password using the PASSWORD\_RSET jumper
- B. Issue password reset from a connected blade's iDRAC
- C. Call Dell tech support and ask to reset CMC password via SupportAssist
- D. Access CMC through serial console and issue theenable secretcommand

Correct Answer: A

---

**QUESTION 3**

An engineer needs to limit the power consumption of a chassis without powering down any server nodes.

Which step should the engineer take to perform this task?

- A. Use the CMC to configure the System Input Power Cap for the chassis
- B. Use the iDRAC to configure the Power Cap Policy for each server node
- C. Use the CMC to configure the Power Cap Policy for each server node
- D. Use the iDRAC to configure the System Input Power Cap for the chassis

Correct Answer: B

---

**QUESTION 4**

**Exhibit**

```
Copyright (C) 2015 QLogic Corporation
FCoE Boot v7.12.4

Starting DCBX process with interface (44:AB:42:DD:85:33) ... Succeeded
Discovering FC Fabric with interface (44:AB:42:DD:85:33) ... Succeeded

World Wide Node Name : 20:00:44:AB:42:DD:85:33
World Wide Port Name : 20:01:44:AB:42:DD:85:33
Fabric Name          : 10:00:F8:BC:12:26:D6:E0
FCF MAC Address      : F8:B1:56:76:BC:00
FP MAC Address       : 0E:FC:00:01:1A:04
VLAN ID              : 1002

Fabric Login via interface (44:AB:42:DD:85:33) ... Succeeded
Locating FC port ID for 00:00:00:00:00:00:00:00 ... Failed

Press <Ctrl-R> within 4s to enter Provisioning Mode... _
```

Refer to the exhibit.

An engineer sets up FCoE boot on their server. The server fails during post.

What needs to be added to the NIC settings/option ROM to make booting successful?

- A. The WWN of the FIP snooping bridge
- B. The WWN of the storage target
- C. The WWN of the FC port ID
- D. The WWN of the fibre channel switch

Correct Answer: C

**QUESTION 5**

In VRTX the following features are enabled:

1.  
Server Module Firmware Update
2.  
Remote syslog
- 3.

iDRAC Single Sign-on.

4.

Server configuration

5.

Chassis grouping

6.

Enclosure level backup Which license type is required?

A. CMC enterprise license

B. CMC express license

C. iDRAC express license

D. iDRAC enterprise license

Correct Answer: A

[DCPPE-200 PDF Dumps](#)

[DCPPE-200 Study Guide](#)

[DCPPE-200 Exam  
Questions](#)