

## DES-1121<sup>Q&As</sup>

Specialist - Implementation Engineer PowerMax and VMAX Family  
Solutions Version 1.0

**Pass EMC DES-1121 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/des-1121.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



### QUESTION 1

Production work has been started on the R2 devices after an 5RDF Failover operation. Where will the changes made to the R2 devices be reflected in the SRDF Query output shown in the exhibit?

Target (R2) View				Source (R1) View				MODE	
Standard	Logical	ST		LI	ST				
Device	Sym	T R1 Inv	R2 Inv	N	A	K Sym	T R1 Inv	R2 Inv	RDF Pair
Dev	Dev	E Tracks	Tracks	S Dev	E Tracks	Tracks	MACE	STATE	
DEV001	00087	1	2	00059	3	4	S...		
DEV002	00088			0005A			S...		

- A. 1
- B. 2
- C. 3
- D. 4

Correct Answer: A

### QUESTION 2

When creating SRDP groups, what is always identical on both the participating arrays?

- A. Port speed
- B. Name of the SRDF group
- C. SRDF group number
- D. SRDF Directors

Correct Answer: C

### QUESTION 3

What are the default settings for a Storage Group in PowerMax, VMAX All Flash, and VMAX3?

- A. No SRP and no SL
- B. Default SRP and no SL
- C. Default SRP and Optimized SL

D. No SRP and Optimized SL

Correct Answer: C

---

#### QUESTION 4

A systems administrator has decommissioned a host with two devices allocated to it. What must the administrator do prior to deleting the devices?

- A. Remove the device attribute
- B. Unmap from the front-end ports
- C. Remove the Storage Group
- D. Delete the Initiators

Correct Answer: C

---

#### QUESTION 5

What is a recommendation when using Open Replicator to migrate data from a supported third-party array to a VMAX3 array?

- A. Host I/O to the control devices on the VMAX3 array is allowed after the migration completes
- B. Control devices on the VMAX3 array must be set to Not Ready for the duration of the migration
- C. Host I/O to the remote devices on the third-party array can continue during the migration
- D. Host I/O to the remote devices on the third-party array should be stopped for the duration of the migration

Correct Answer: D

[DES-1121 VCE Dumps](#)

[DES-1121 Study Guide](#)

[DES-1121 Braindumps](#)