

DES-1721^{Q&As}

Specialist - Implementation Engineer-SC Series Exam

Pass EMC DES-1721 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/des-1721.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

You are implementing a front-end connection in Legacy Port Mode on an SC4020 in a SAN with two iSCSI switches. What is the minimum number of port(s), per switch, that can be used by each controller?

- A. One port on each Ethernet switch
- B. Two ports on each Ethernet switch
- C. Four ports on each Ethernet switch
- D. Eight ports on each Ethernet switch

Correct Answer: C

QUESTION 2

Which command is used to assign the DNS server IP address 10.10.10.12 on an SC9000 during the initial configuration?

- A. controller ipconfig 10.10.10.12
- B. net dns init 10.10.10.12
- C. controller dnsserver 10.10.10.12
- D. ifconfig inet 10.10.10.12

Correct Answer: B

Reference: <https://www.dell.com/community/Compellent/Dell-SC4020/td-p/5036791>

QUESTION 3

DRAG DROP

What is order of steps that the Storage Center will follow when it senses that the UPS has lost input power?

Select and Place:

Internal write cache is re-enabled	STEP 1
Internal write cache is disabled	STEP 2
UPS signals it is running from battery	STEP 3
AC power is restored	STEP 4
All write operations are committed to disk	STEP 5

Correct Answer:

	UPS signals it is running from battery
	All write operations are committed to disk
	Internal write cache is disabled
	AC power is restored
	Internal write cache is re-enabled

QUESTION 4



Refer to the exhibit.

Starting in the upper left corner of the SCv3000 what is the numerical order of the disks across the top row?

- A. 3, 2, 1, 0
- B. 4, 3, 2, 1
- C. 1, 2, 3, 4
- D. 0, 1, 2, 3

Correct Answer: D

Reference: https://be02.cp-static.com/objects/pdf/f/f26/1792753_1_disk-arrays-dell-scv3020-3020-2604.pdf (Page 8)

QUESTION 5

Which command is used to set the eth0 IP address on an SC4020 controller?

- A. `ifconfig inet eth0 [IP address] [netmask] [gateway]`
- B. `controller ipconfig eth0 [IP address/prefix length]`
- C. `ifconfig inet eth0 [IP address/prefix length]`
- D. `controller ipconfig eth0 [IP address] [netmask] [gateway]`

Correct Answer: C

Reference: <https://www.dell.com/community/Compellent/Dell-SC4020/td-p/5036791>

[DES-1721 PDF Dumps](#)

[DES-1721 Practice Test](#)

[DES-1721 Exam Questions](#)