

DES-4421^{Q&As}

Specialist - Implementation Engineer, PowerEdge MX Modular Exam

Pass EMC DES-4421 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/des-4421.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Refer to the exhibit.



How many internal server-facing ports are available on this I/O module for the MX7000 chassis?

- A. 2
- B. 8
- C. 16
- D. 24

Correct Answer: C

Reference: https://i.dell.com/sites/csdocuments/Product_Docs/en/dell_emc_poweredge_mx7000_technical_guide.pdf

QUESTION 2

A technician replaces a failed Management Module in an MX7000 chassis group. After the technician leaves the site, the administrator reports that the lead chassis is no longer able to communicate with its members. How can OME-M be used to confirm the cabling configuration?

- A. View the health status of the lead Chassis Management Module
- B. View the health status of the lead Chassis Management ports
- C. View the I/O module topology map from the lead chassis
- D. View the topology map from the Group Lead

Correct Answer: B

QUESTION 3

An MX7000 administrator has been tasked to create a Scalable Fabric Architecture on a 3 chassis setup using Fabric B. Which IOM configuration is recommended?

- A. Chassis 1 - Slot B1: MX9116n; Slot B2: MX9116n Chassis 2 - Slot B1: MX5108n; Slot B2: MX5108n Chassis 3 - Slot B1: MX5108n; Slot B2: MX5108n
- B. Chassis 1 - Slot B1: MX7116n; Slot B2: MX7116n Chassis 2 - Slot B1: MX7116n; Slot B2: MX7116n Chassis 3 - Slot B1: MX9116n; Slot B2: MX9116n

C. Chassis 1 - Slot B1: MX9116n; Slot B2: MX7116n Chassis 2 - Slot B1: MX7116n; Slot B2: MX9116n Chassis 3 - Slot B1: MX7116n; Slot B2: MX7116n

D. Chassis 1 - Slot B1: MX9116n; Slot B2: MX5108n Chassis 2 - Slot B1: MX5108n; Slot B2: MX9116n Chassis 3 - Slot B1: MX5108n; Slot B2: MX5108n

Correct Answer: A

QUESTION 4

What can be used as the firmware update source for OME-M within an MX chassis?

- A. Server Update Utility Baseline from a Catalog
- B. Server Update Utility System Live Image (SLI)
- C. Dell Update package System Live Image (SLI)
- D. Dell Update Package Baseline from a Catalog

Correct Answer: D

Reference: https://topics-cdn.dell.com/pdf/openmanage-enterprise-modular-v10001-poweredge-mx7000_users-guide4_en-us.pdf

QUESTION 5

What automatically opens a support case with technical support and collects the PowerEdge MX system state information that is required for troubleshooting an issue, then sends it securely to Dell EMC?

- A. OpenManage Essentials
- B. SupportAssist Collections
- C. OpenManage Enterprise
- D. SupportAssist Enterprise

Correct Answer: D

[DES-4421 Practice Test](#)

[DES-4421 Study Guide](#)

[DES-4421 Exam Questions](#)