

DES-4421^{Q&As}

Specialist - Implementation Engineer, PowerEdge MX Modular Exam

Pass EMC DES-4421 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/des-4421.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

DRAG DROP

A technician is deploying a new MX7000 chassis using the Chassis Deployment Wizard.

What is the correct order o steps followed by the wizard?

Select and Place:

Configure iDRAC and IOM Quick Deploy Settings	STEP 1
Import Profile or join Multi-chassis Group	STEP 2
Configure Activity and Alerts	STEP 3
Define Groups	STEP 4
Update Firmware and configure Proxy	STEP 5

Correct Answer:

	Import Profile or join Multi-chassis Group
	Configure Activity and Alerts
	Configure iDRAC and IOM Quick Deploy Settings
	Update Firmware and configure Proxy
	Define Groups

QUESTION 2

An administrator is about to perform a firmware update on an MX9116n switch OS 10 from the CLI. The latest OS 10 switch firmware image has been downloaded and their TFTP server is set up. Upon logged in with administrator credentials on the switch, which command should be used to start the update procedure?

- A. firmwaredownload tftp://server-ip/imagename
- B. install tftp://server-ip/imagename

C. fwupdate tftp://server-ip/imagename

D. upgrade tftp://server-ip/imagename

Correct Answer: B

Reference: https://topics-cdn.dell.com/pdf/smartfabric-os10-5-0_en-us.pdf

QUESTION 3

Which controller option the mapping of an entire MX5016s to multiple compute sleds?

A. PERC H730 only

B. HBA330 only

C. H745 Jumbo PERC

D. HBA330 and PERC H730

Correct Answer: B

Reference: https://www.dell.com/support/manuals/us/en/04/poweredge-mx7000/pemx5016s_mx5000s_ism/initial-system-setup-and-configuration-for-mx5016s?guid=guid-f5a47d05-b0f9-4573-aa98-350a7e7a2c3candlang=en-us

QUESTION 4

At the initial release of the MX7000 for a daisy-chained configuration in a multi-chassis management group (MCM) what is the maximum number of member chassis allowed, not counting the lead chassis?

A. 9

B. 10

C. 16

D. 20

Correct Answer: A

Reference: https://www.dell.com/support/manuals/us/en/04/poweredge-mx7000/omem1.00.01_ug/chassis-groups?guid=guid-967e1786-b148-45f6-8184-c6a70296483aandlang=en-us

QUESTION 5

A new administrator has just taken over an MX7000 Multi-Chassis Management Group and two-racks of PowerEdge servers. The previous administrator no longer works at the company and is not available. No one knows the password for the OME-M interface and the default password is not working.

What must be used to reset the password?

- A. iDRAC for one of the compute sleds.
- B. Left ear control panel.
- C. RACADM using a serial connection
- D. Management Module jumpers

Correct Answer: D

Reference: https://www.dell.com/support/manuals/us/en/04/poweredge-mx7000/omem1.00.01_ug/recovering-passwords?guid=guid-553bf2dd-c491-4117-85f5-c2fbfde4ef12andlang=en-us

[DES-4421 VCE Dumps](#)

[DES-4421 Practice Test](#)

[DES-4421 Study Guide](#)