

DES-5121^{Q&As}

Specialist - Implementation Engineer - Campus Networking Exam

Pass EMC DES-5121 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/des-5121.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which port security method converts existing dynamically learned MAC addresses on an interface to this mode and not age out?

- A. Static
- B. MAC address
- C. Sticky
- D. Dynamic

Correct Answer: D

Reference: <https://www.dell.com/support/manuals/us/en/04/networking-s4148f-on/smartfabric-os-user-guide-10-5-1/port-security?guid=guid-c27a9d47-ea59-48cc-b19d-90a9f6d52629&lang=en-us>

QUESTION 2

When setting up VoIP, you decide that you want to use LLDP. LLDP is enabled by default and LLDP Transmit Management Information and Notification modes are enabled.

What additional steps need to be performed?

- A. Enable ISDP and enable LLDP-MED confignotification
- B. Disable ISDP and enable LLDP-MED confignotification
- C. Enable ISDP and disable LLDP-MED confignotification
- D. Disable ISDP and disable LLDP-MED confignotification

Correct Answer: B

QUESTION 3

After setting up the VoIP configuration, a network administrator issues the following commands with the results shown:

```
console# show voice vlan Administrative Mode.....Enable
```

```
console# show voice vlan it gi 1/0/2
```

```
Interface.....Gi1/0/2
```

```
Voice VLAN Interface Mode.....Enabled
```

```
Voice VLAN ID.....10
```

```
Voice VLAN COS Overwrite.....False
```

Voice VLAN DSCP Value.....46

Voice VLAN Port Status.....Enabled

Voice VLAN Authentication.....Disabled

Based on this information, what is the Layer 3 QoS value?

- A. 5
- B. 10
- C. 46
- D. Gi1/0/2

Correct Answer: C

QUESTION 4

Refer to the Exhibit.

```
Switch-1(config)# radius server host 10.1.1.111 Switch-1(config-radius)# key "secretkey" Switch-1(config-radius)# exit
Switch-1(config)# aaa authentication login "LOCAL-AUTH" local Switch-1(config)# aaa authentication login "REMOTE-
AUTH" radius local Switch-1(config)# aaa authentication enable "REMOTE-AUTH" radius enable Switch-1(config)# aaa
authentication login default tacacs local Switch-1(config)# aaa authentication enable default tacacs enable
Switch-1(config)# line telnet Switch-1(config-telnet)# login authentication "REMOTE-AUTH" Switch-1(config-telnet)# exit
Switch-1(config)# line ssh Switch-1(config-ssh)# login authentication default Switch-1(config)# exit Switch-1(config)# line
console Switch-1(config-line)# login authentication "LOCAL-AUTH" Switch-1(config-line)# exit
```

Which authentication method will be used if a user tries to log into the switch when accessing through SSH?

- A. RADIUS, then fails over to a local user account
- B. Local user account
- C. TACACS, then fails over to a local user account
- D. None

Correct Answer: C

QUESTION 5

Which function does a VRRP backup router perform?

- A. Sends keepalive advertisements to the other backup routers
- B. Processes and responds to ARP requests
- C. Forwards packets to the Master with a destination IP of the virtual IP address
- D. Receives packets with the virtual MAC address as the destination for other backup routers

Correct Answer: D

[Latest DES-5121 Dumps](#)

[DES-5121 VCE Dumps](#)

[DES-5121 Exam Questions](#)