

DES-5121^{Q&As}

Specialist - Implementation Engineer - Campus Networking Exam

Pass EMC DES-5121 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leadspass.com/des-5121.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

If a VRRP Master router is rebooted, what is the default behavior once it comes back online?

- A. An election occurs to determine which router will have the Master role
- B. Original VRRP Master will take back control of the Master role
- C. Original VRRP Backup will retain the Master role
- D. VRRP Master role is determined by the router with the lowest MAC address

Correct Answer: B

QUESTION 2

In a PoE environment, what information does the Network Policy TLV exchange between the PSE and PD?

- A. Required Power, VLAN ID, and DSCP Value
- B. VLAN ID, IEEE Priority, and DSCP Value
- C. IEEE Priority, Required Power, and VLAN ID
- D. DSCP Value, Required Power, and IEEE Priority

Correct Answer: B

Reference: http://ftp.dell.com/manuals/all-products/esuprt_ser_stor_net/esuprt_networking/poweredge-m-io-aggregator_Concept-Guide4_en-us.pdf page 162

QUESTION 3

Which function does a VRRP backup router perform?

- A. Sends keepalive advertisements to the other backup routers
- B. Processes and responds to ARP requests
- C. Forwards packets to the Master with a destination IP of the virtual IP address
- D. Receives packets with the virtual MAC address as the destination for other backup routers

Correct Answer: D

QUESTION 4

A switch interface has been properly configured for static port security with one defined allowable MAC address. However, when the network administrator plugs a switch into that port, multiple devices are still allowed access to the

network. Where must port security also be enabled to have an effect?

- A. Enabled globally on the switch
- B. Enabled on all attached devices
- C. Enabled on all switches in the network
- D. Enabled on all interfaces of the switch

Correct Answer: A

Reference: <https://www.dell.com/support/article/en-us/how10392/how-to-configure-mac-based-port-security-on-dell-n2000-n3000-and-n4000-series-switches?lang=en>

QUESTION 5

A user's host with an IP address of 172.16.1.22/24 is attempting to FTP a file from the server with IP address 10.1.1.99; however, they are unable to connect.

Which access-list is preventing this traffic?

- A. # ip access-list ACL1 # deny ip any host 10.1.1.99
- B. # ip access-list ACL2 # permit ip 172.16.1.0 0.0.0.255 any
- C. # ip access-list ACL3 # deny ip any 172.16.2.0 0.0.0.255
- D. # ip access-list ACL4 # permit ip host 172.16.1.22 host 10.1.1.99

Correct Answer: A

[DES-5121 PDF Dumps](#)

[DES-5121 Practice Test](#)

[DES-5121 Study Guide](#)